PRODUCT DATA SHEET PRODUCT CODE: M234400

Nothing 86 System Accent modules LED (GU10) 1x7 W



DESIGN BY


Ernesto Gismondi

DESCRIPTION

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems. 3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed. Linear fluorescent, led and metal halide technologies can be freely alternated. Pre-wired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination. 2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots. 2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards.

Glow Wire Test:

TECHNICAL DRAWINGS



FEATURES

Article Code: M234400
Colour: Black
Installation: Projector
Environment: Indoor

DIMENSIONS

 Length:
 cm 23.7

 Width:
 cm 8.6

 Inclination:
 cm 30

 Rotation:
 cm 355

INCLUDED SOURCES

 Category:
 LED

 Number:
 1

 Watt:
 7W

 Type:
 0

 Class:
 A

LUMINAIRE

Power Supply: Electronic included Watt: 1x7W

Notes

Integrated electronic power supply. Integrated MV through-cabling.

Indoor

850

ACCESSORIES



Supplementary through-wiring (optional). To be used in mixed configuration with LV and MV precabled gear trays. - LV 2368mm. M199000



Supply Kit. Allows for connection of the mains to the first pre-wired gear plate of the initial module. To be used only with recessed and surface installation. - MV (7xmax 1,5 mm2) To power white LED plates and accent modules. M073240



Cablaggio passante supplementare (opzionale) lunghezza 237 mm. M211700



NOTHING 86 SYSTEM - Blind panel. Length 236,8mm (=1L). black M232710



Supply Kit. Allows for connection of the mains to the first pre-wired gear plate of the initial module. To be used only with recessed and surface installation. - LV (3xmax 1,5 mm2) To power LED RGB trays.

M073230



Raccordo su un piano per la contiunuità tra moduli LED a emissione diffusa e tra moduli spot. M167500



Supplementary through-wiring (optional). To be used in mixed configuration with LV and MV precabled gear trays. - LV 1184mm. M198800