


## Pad System Dali+Switch-Dim 3000K - White



IP20 Dimmable: + -

### TECHNICAL DRAWINGS



### DESIGN BY

Carlotta de Bevilacqua

### DESCRIPTION

Pad System is the result of a study on the theme of office lighting, which defines a new way of producing light where functional quality and comfort are the main values. With the innovative patented ALEF (Advanced Light Emitting Film) technology of LG, Pad System upsets the traditional optical approaches (based on reflectors and refractors) used in working environments, which allow to control light emission but, at the same time, result into a non-uniform appearance of the appliance's output surface. With ALEF, a patent derived from TV-screen backlighting systems, Pad System appears as a perfectly uniform luminous surface, capable to control emission over 60° beyond the appliance's ordinary one while ensuring high uniformity values, low luminance levels, and an UGR below 19, according to the provisions of UNI 12464 (luminance at 65° <3000 cd/m<sup>2</sup> - average UGR < 19). The appliance's body has a very thin aluminium edge (90x20mm), which makes Pad System one of the world's slimmest technical office lighting systems. Flexibility is ensured by the joints, which allow to obtain multiple modular configurations.

### FEATURES

<b>Article Code:</b>	M3051W21	<b>Series:</b>	Indoor
<b>Colour:</b>	White	<b>Area contract:</b>	Hospitality, null, Retail, Culture, Residential
<b>Installation:</b>	Suspension		

### DIMENSIONS


<b>Length:</b>	cm 120
<b>Width:</b>	cm 19
<b>Height:</b>	cm 1.6

### INCLUDED SOURCES


<b>Category:</b>	LED	<b>Color temperature (K):</b>	3000K
<b>Number:</b>	1	<b>CRI:</b>	80
<b>Watt:</b>	33W	<b>Efficacy:</b>	116lm/W
<b>Delivered lumens output (lm):</b> 3780lm			
<b>Type:</b> 0			
<b>Class:</b> A			

### LUMINAIRE


<b>Watt:</b>	39W	<b>Delivered lumens output (lm):</b>	3062lm
<b>CCT:</b>	3000K		
<b>Efficiency:</b>	81%		
<b>Efficacy:</b>	78.50lm/W		
<b>CRI:</b>	80		

**ACCESSORIES**


Kit driver linear connector - 1M.  
Occupies 1 DALI destination  
M305521




Kit driver linear connector - 2M.  
Occupies 1 DALI destination  
M305621



Kit driver linear and angular connector - 1M. + 1M. Occupies 1 DALI destination  
M305721



Kit driver linear and angular connector - 1M. + 2M. Occupies 2 DALI destinations  
M305821



Kit driver linear and angular connector - 2M. + 2M. Occupies 2 DALI destinations  
M305921




PadSystem\_End\_Cap\_White  
M305220



PadSystem\_L-shaped\_Connector\_White  
M305320



PadSystem\_90°\_Shaped\_Connector\_White  
M305420



Recessed kit for roses - 1/2/3/4 modules  
M300900