


Pad System Dali+Switch-Dim 4000K - White



IP20 💮 Dimmerable: +①-

TECHNICAL DRAWINGS



DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Pad System is the result of a study on the theme of office lighting, which defines a new way of producing light where functional quality and comfort are the main values. With the innovative patented ALEF (Advanced Light Emitting Film) technology of LG, Pad System upsets the traditional optical approaches (based on reflectors and refractors) used in working environments, which allow to control light emission but, at the same time, result into a non-uniform appearance of the appliance's output surface. With ALEF, a patent derived from TV-screen backlighting systems, Pad System appears as a perfectly uniform luminous surface, capable to control emission over 60° beyond the appliance's ordinary one while ensuring high uniformity values, low luminance levels, and an UGR below 19, according to the provisions of UNI 12464 (luminance at 65° <3000 cd/m2 – average UGR < 19). The appliance's body has a very thin aluminium edge (90x20mm), which makes Pad System one of the world's slimmest technical office lighting systems. Flexibility is ensured by the joints, which allow to obtain multiple modular configurations.

FEATURES			
Article Code: Colour: Installation:	M3051N21 White Suspension	Series: Area contract:	Indoor Hospitality, null, Retail, Culture, Residential
DIMENSIONS			
Length: Width: Height:	cm 120 cm 19 cm 1.6		
INCLUDED SOURC	CES		
Category: Number: Watt: Delivered lumens out Type: Class:	LED 1 33W put (Im): 4320Im 0 A	Color temperature (K): CRI: Efficacy:	4000K 80 133lm/W
LUMINAIRE			
Watt:	39W	Delivered lumens output (CCT: Efficiency: Efficacy:	lm): 3499lm 4000K 81% 89.72lm/W

CRI:

Dimmable Typology:

80

Dali



PRODUCT CODE: M3051N21

ACCESSORIES

o	215
424	_
	115
	1 114
lit driver lir	near

connector - 1M. Occupies 1 DALI destination M305521



Kit driver linear and angular connector - 1M. + 2M. Occupies 2 DALI destinations M305821



connector - 2M. Occupies 1 DALI destination M305621



and angular connector - 2M. + 2M. Occupies 2 DALI destinations M305921



M305420



PadSystem_90°_Shaped_Connector_WRiteessed kit for

roses - 1/2/3/4 modules M300900



Kit driver linear and angular connector - 1M. + 1M. Occupies 1 DALI destination M305721



PadSystem_End_Cap_White M305220



PadSystem_Lshaped_Connector_White M305320