


PRODUCT DATA SHEET

Picto 70 LED track vertical - white 35° 3000K - Dali



TECHNICAL DRAWINGS



DESIGN BY

Studio Artemide

DESCRIPTION

This range of professional projectors is distinguished by design, excellent performance and flexibility. Picto is a complete and versatile range, suitable for use in retail spaces, showrooms, museums or art galleries. Available in 3 sizes, installation options, designs, colours, optics and a wide range of accessories.

Article Code:AD03101Material:aluminumColour:WhiteSeries:IndoorInstallation:Projector, Track, CeilingArea contract:Hospitality, Retail, CultureEnvironment:IndoorDIMENSIONSInclination:cm 7.8 (m 21.5)Glow Wire Test:850Length:cm 21.5 (m 21.5)Glow Wire Test:850Weight:kg 1.2 (nclination:-90+90 (m 355)Service Life:3000 KINCLUDED SOURCESColor temperature (K): (Color Tolerance:3000 KNumber:1 (Color Tolerance:MacAdam 2SDCMVatt:20 W (Class:Service Life:Life L70 (6K) 50000hType:0 (Class:ACelivered lumens output (lm): 1753lm (CCT:Power Supply:Power supply 220/240Vac 50/60Hz includedDelivered lumens output (lm): 1753lm (CCT:3000 KWatt:20WEfficiency: (CST:86% (SM)Watt:20WEfficiency: (CR):90	FEATURES			
Colour:White Projector, Track, CeilingSeries:IndoorInstallation:Projector, Track, CeilingArea contract:Hospitality, Retail, CultureEnvironment:IndoorHoorDIMENSIONSSeries:SolutureLength:cm 7.8 cm 21.5Glow Wire Test:850Height:cm 21.5SolutureSolutureVeight:kg 1.2 rodation:-90+90SolutureSolutureInclination:-90+90color temperature (K):3000 KKumber:1Color Tolerance:MacAdam 2SDCMVatt:20 WService Life:Life L70 (6K) 50000hType:0Color temperature (K):3000 KClass:AService Life:Life L70 (6K) 5000hLUMINAIREPower Supply:Power supply 200/240/vac 50/60HzDelivered lumens output (Im:1753Im 200/240/wac 50/60HzWatt:20WEfficiency:36%Watt:20WEfficiency:86%		AD03101	Material:	aluminum
Installation: Projector, Track, Ceiling Environment: Indoor DIMENSIONS Length: cm 7.8 Glow Wire Test: 850 Height: cm 21.5 Weight: kg 1.2 Inclination: -90+90 Rotation: cm 355 INCLUDED SOURCES Color temperature (K): 3000 K Mumber: 1 Color Tolerance: MacAdam 2SDCM Watt: 20 W Color Tolerance: MacAdam 2SDCM Vatt: 20 W LED Color Tolerance: Life L70 (6K) 50000h Type: 0 Class: A LUMINAIRE Power Supply: Power supply 20/240/vac 50/60Hz included Efficiency: 86% Watt: 20W				
Ceiling IndoorCultureEnvironment:IndoorDIMENSIONSCur 7.8Glow Wire Test:850Length: Height: weight: Inclination: Rotation:cm 21.5Souther State850INCLUDED SOURCEScm 355Glow Wire Test:850INCLUDED SOURCESColor temperature (K): Color Tolerance:3000 KNumber: Watt: Type: Class:LED 0 Color Tolerance:MacAdam 2SDCMLUMINAIREService Life:Life L70 (6K) 50000hPower Supply: IncludedPower supply 220/240Vac 50/60HzDelivered lumens output (Im: 1753Im 220/240Vac 50/60HzWatt: Color Supply:Delivered lumens output (Im: 1753Im 220/240Vac 50/60HzService Life: Service Life:Watt:20WEfficiency: Service86% Service				
Environment: Indoor DIMENSIONS Length: cm 7.8 cflow Wire Test: 850 Height: cm 21.5 Weight: kg 1.2 Inclination: -90+90 Rotation: cm 355 INCLUDED SOURCES Category: LED Color temperature (K): 3000 K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 20 W Service Life: Life L70 (6K) 50000h Type: 0 Class: A LUMINAIRE Power Supply: Power supply 200240Vac 50/60Hz cfficiency: 86% Watt: 20W Efficiency: 86%	instantion.			
Length:cm 7.8 cm 21.5 kg 1.2 Inclination:Glow Wire Test:850Weight:kg 1.2 rom 355kg 1.2 rom 355Solution:Solution:INCLUDED SOURCEScm 355Solution:Solution:Category:LED rom 355Color temperature (K):3000 K MacAdam 2SDCM MacAdam 2SDCMNumber:1 rom 20 W rom 20 WColor Tolerance: Service Life:MacAdam 2SDCM Life L70 (6K) 50000h Life L70 (6K) 50000hType:0 class:ALife L70 (6K) 50000h class:LUMINAIREPower supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 1753Im 200K Efficiency:Solution:Watt:20WEfficiency:86% 87.63Im/W	Environment:	0		calcale
Length:cm 7.8 cm 21.5 kg 1.2 Inclination:Glow Wire Test:850Weight:kg 1.2 rom 355kg 1.2 rom 355kg 1.2 rom 355kg 1.2 rom 355kg 1.2 rom 355INCLUDED SOURCEScm 355cm 355INCLUDED SOURCESLED Color temperature (K):3000 K MacAdam 2SDCM Vatt:Vatt:20 W rom 20 WService Life:Life L70 (6K) 50000h rom 25000hType:0 class:ALUMINAIREPower supply 220/240Vac 50/60Hz includedDelivered lumens output (Im): 1753Im 200K Efficiency:1753Im 86% 86%Watt:20WEfficiency:86% 87.63Im/W				
Height:cm 21.5cm 21.5Weight:kg 1.2Inclination:-90+90Rotation:cm 355INCLUDED SOURCESColor temperature (K):3000 KCategory:LEDColor Tolerance:MacAdam 2SDCMWumber:1Color Tolerance:MacAdam 2SDCMVatt:20 WService Life:Life L70 (6K) 50000hType:0Color Tolerance:MacAdam 2SDCMLUMINAIREPower supply:Delivered lumens output (lm): 1753lmPower Supply:Power supplyDelivered lumens output (lm): 1753lmMatt:220/240Vac 50/60HzCCT:3000KWatt:20WEfficiency:86%	DIMENSIONS			
Weight:kg 1.2Inclination:-90+90Rotation:cm 355INCLUDED SOURCESColor temperature (K):3000 KCategory:LEDColor Tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMVatt:20 WService Life:Life L70 (6K) 50000hType:0Color Tolerance:IncludedLUMINAIREPower supply:Power supplyDelivered lumens output (Im): 1753ImPower Supply:Power supplyDelivered lumens output (Im): 1753ImCT:3000KincludedEfficiency:86%Watt:20WEfficiency:87.63Im/W	Length:	cm 7.8	Glow Wire Test:	850
Inclination:-90+90 Rotation:Rotation:-90+90 cm 355INCLUDED SOURCESImage: Color temperature (K):3000 K MacAdam 2SDCMCategory:LEDColor tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMVatt:20 WService Life:Life L70 (6K) 50000hType:0Color Tolerance:MacAdam 2SDCMClass:ADelivered lumens output (Im): 1753Im 220/240Vac 50/60HzCCT:Power Supply:Power supply includedDelivered lumens output (Im): 1753Im CCT:2000KWatt:20WEfficiency:86% 87.63Im/W	Height:	cm 21.5		
Rotation:cm 355INCLUDED SOURCESColor temperature (K):3000 KCategory:LEDColor Tolerance:MacAdam 2SDCMNumber:1Color Tolerance:MacAdam 2SDCMWatt:20 WService Life:Life L70 (6K) 50000hType:0Class:ALUMINAIREPower supplyDelivered lumens output (Im): 1753ImPower Supply:Power supplyDelivered lumens output (Im): 1753ImMatt:200WEfficiency:86%Watt:20WEfficiency:86%	Weight:	kg 1.2		
INCLUDED SOURCESCategory:LEDColor temperature (K):3000 KNumber:1Color Tolerance:MacAdam 2SDCMWatt:20 WService Life:Life L70 (6K) 50000hType:0Service Life:Life L70 (6K) 50000hClass:AEuler Color Tolerance:Life L70 (6K) 50000hLUMINAIREPower supplyDelivered lumens output (Im): 1753ImPower Supply:Power supply includedCCT:3000KEfficiency:86%Watt:20WEfficiency:87.63Im/W	Inclination:	-90+90		
Category: LED Color temperature (K): 3000 K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 20 W Service Life: Life L70 (6K) 50000h Type: 0 Class: A LUMINAIRE Power supply Delivered lumens output (Im): 1753Im 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 86% Watt: 20W Efficiacy: 87.63Im/W	Rotation:	cm 355		
Category: LED Color temperature (K): 3000 K Number: 1 Color Tolerance: MacAdam 2SDCM Watt: 20 W Service Life: Life L70 (6K) 50000h Type: 0 Class: A LUMINAIRE Power supply Delivered lumens output (Im): 1753Im 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 86% Watt: 20W Efficiacy: 87.63Im/W				
Number:1Color Tolerance:MacAdam 2SDCMWatt:20 WService Life:Life L70 (6K) 50000hType:0Service Life:Life L70 (6K) 50000hClass:AEEDelivered Limens output (Im): 1753Im220/240Vac 50/60HzCT:3000KincludedEfficiency:86%Watt:20WEfficiecy:87.63Im/W	INCLUDED SOURCES			
Watt: 20 W Service Life: Life L70 (6K) 50000h Type: 0 Class: A LUMINAIRE Power supply Delivered lumens output (lm): 1753Im 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 86% Watt: 20W Efficacy: 87.63Im/W	Category:	LED	Color temperature (K):	3000 K
Type: 0 Class: A LUMINAIRE Power Supply: Power supply 220/240Vac 50/60Hz included Efficiency: 86% Watt: 20W Efficacy: 87.63lm/W	Number:	1	Color Tolerance:	MacAdam 2SDCM
Class: A LUMINAIRE Power Supply: Power supply 220/240Vac 50/60Hz included Delivered lumens output (lm): 1753Im CCT: 3000K Efficiency: 86% Watt: 20W Efficacy: 87.63Im/W	Watt:	20 W	Service Life:	Life L70 (6K) 50000h
LUMINAIRE Power supply Delivered lumens output (lm): 1753Im 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 86% Watt: 20W Efficacy: 87.63lm/W	Туре:	0		
Power Supply: Power supply Delivered lumens output (lm): 1753lm 220/240Vac 50/60Hz CCT: 3000K included Efficiency: 86% Watt: 20W Efficacy: 87.63lm/W	Class:	А		
220/240Vac 50/60Hz CCT: 3000K included Efficiency: 86% Watt: 20W Efficacy: 87.63lm/W	LUMINAIRE			
220/240Vac 50/60Hz CCT: 3000K included Efficiency: 86% Watt: 20W Efficacy: 87.63lm/W	Power Supply:	Power supply	Delivered lumens output (lm)	: 1753lm
included Efficiency: 86% Watt: 20W Efficacy: 87.63lm/W		11.5		
Watt: 20W Efficacy: 87.63lm/W				
	Watt:		•	
				90

Dimmable Typology:

Dali



PRODUCT CODE: AD03101

ACCESSORIES



Accessory-holder (nero) + projection lens and framing device M083937



Accessory-holder (black) + Projection lens for gobo. Customized gobo to be ordered separately M083837



Accessory-holder (black) + Adjustable dowser (black) M082837



Accessory-holder (black) + wall washer screen (black) M083037



Accessory for ceiling installation (white) L176320