

PRODUCT DATA SHEET

Sharp - 33W 54° 4000K Trim Silver



IP20 💮 ce

TECHNICAL DRAWINGS



DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

FEATURES			
Article Code: Colour: Installation: Environment:	AF20505 Silver Recessed, Ceiling Indoor	Series:	Indoor
DIMENSIONS			
Length: Width: Height:	cm 46 cm 5.5 cm 5.5		
INCLUDED SOURCES			
Category: Number: Watt: Type: Class:	LED 1 33W 0 A	Color temperature (K):	4000K
LUMINAIRE			
Watt:	33W	Delivered lumens output (lm) CCT: Efficiency: Efficacy:	: 2501lm 4000K 73% 75.79lm/W

CRI:

90



PRODUCT CODE: AF20505

ACCESSORIES



AF95201



Driver 55 W 900mA DV1007





Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses. AF06000



Driver 50 W 900mA DV1005