3000K

PRODUCT DATA SHEET

Sharp - 3W 34° 3000K Trim Silver



IP20 ⟨ () €


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

TECHNICAL DRAWINGS



FEATURES

Article Code: AF00405 Series: Indoor
Colour: Silver
Installation: Recessed, Ceiling
Environment: Indoor

Color temperature (K):

DIMENSIONS

 Length:
 cm 5.3

 Width:
 cm 5.5

 Height:
 cm 5.5

INCLUDED SOURCES

 Category:
 LED

 Number:
 1

 Watt:
 3W

 Type:
 0

 Class:
 A

LUMINAIRE

 Watt:
 3W
 Delivered lumens output (Im): 188Im

 CCT:
 3000K

 Efficiency:
 71%

 Efficacy:
 62.68Im/W

CRI:

PRODUCT DATA SHEET

ACCESSORIES



Screen 1x White AF95001

NO IMAGE AVAILABLE

Driver 25,2 W 900mA DV1003



Screen 1x Black AF95004

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of \$ 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000



Driver 7,2W 900mA DV1001