Indoor

2700K



PRODUCT DATA SHEET

Sharp SMD - 11W 54° 2700K White



DESIGN BY

Carlotta de Bevilacqua


DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

Series:

Color temperature (K):

TECHNICAL DRAWINGS



FEATURES

Article Code:	AF41201
Colour:	White
Installation:	Ceiling
Environment:	Indoor

DIMENSIONS

Length:	cm 15.2
Width:	cm 4.5
Height:	cm 9

INCLUDED SOURCES

Category.	LED
Number:	1
Watt:	11W
Type:	0
Class:	Α

LUMINAIRE

Watt:	11W	Delivered lumens output (lm): 731ln	
		CCT:	2700K
		CRI:	>90

Notes

Screen and CV SELV driver supplied separately.



ACCESSORIES

NO IMAGE AVAILABLE

Driver CV 30W 24Vdc Selv - 220-240 Vac -153x41x32 (LxWxH) - up to 25W -Undimmable DV1032



Screen 4x White AF95201



Screen 4x Black AF95204

NO IMAGE AVAILABLE

Driver CV 75W 24Vdc Selv - 220-240 Vac -180x52x30 (LxWxH) - up to 65W -Undimmable DV1009 NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of \$ 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000

NO IMAGE AVAILABLE

Driver CV 120W 24Vdc Selv - 220-240 Vac -153x41x32 (LxWxH) - up to 100W -Undimmable DV1033