

PRODUCT DATA SHEET

Sharp SMD - 33W 54° 3000K Silver




DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

TECHNICAL DRAWINGS



FEATURES

Article Code: Colour: Installation: Environment: DIMENSIONS	AF81205 Silver Ceiling Indoor	Series:	Indoor
Length: Width: Height: INCLUDED SOURCES	cm 44.8 cm 4.5 cm 9		
Category: Number: Watt: Type: Class:	LED 1 33W 0 A	Color temperature (K):	3000К

LUMINAIRE

Watt:	36W	Delivered lumens output (lm): 2337lm	
		CCT:	3000K
		Efficiency:	73%
		Efficacy:	64.91lm/W
		CRI:	90

Notes

Screen and CV SELV driver supplied separately.



ACCESSORIES



Screen 4x Black AF95204



Screen 4x White AF95201

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of S 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000