Indoor

4000K



PRODUCT DATA SHEET

Sharp SMD - 33W 54° 4000K Silver



DESIGN BY

Carlotta de Bevilacqua


DESCRIPTION

High-efficiency patented optical system that combines polynomial perspective to an element that shields geometrically the angle of vision of the beam. High uniformity of illumination and full emission control. Complete absence of possible light flaws as stains and multi-shadows. Recessed depth 60 mm. Suitable for a ceiling of 1 to 25 mm. Available in trim versions, trimless and SMD.

Series:

Color temperature (K):

TECHNICAL DRAWINGS



FEATURES

Article Code:	AF81505
Colour:	Silver
Installation:	Ceiling
Environment:	Indoor

DIMENSIONS

Length:	cm 44.8
Width:	cm 4.5
Height:	cm 9

INCLUDED SOURCES

Category:	LED
Number:	1
Watt:	33V
Type:	0
Class:	Α

LUMINAIRE

Watt:	36W	Delivered lumens output (lm): 2501lm	
		CCT:	4000K
		Efficiency:	73%
		Efficacy:	69.47lm/W
		CRI:	90

Notes

Screen and CV SELV driver supplied separately.



ACCESSORIES



Screen 4x Black AF95204



Screen 4x White AF95201

NO IMAGE AVAILABLE

Sharping wall grazer lens Kit (4pcs) - 26°x70° elliptical lenses kit. It has to be used on top of \$ 20° reflectors to get an elliptical beam (greter axis along the module lenght). It contains 4 lenses.

AF06000