


Surf System Led - Undimmable - 3000K - White



IP20 


DESIGN BY

Neil Poulton

DESCRIPTION

A valid alternative to fluorescent modules for general lighting solutions of the tertiary buildings, school premises, public or industrial spaces, and circulation areas, Surf System Led is a more than attractive option easily interchangeable with Surf System fluorescent modules of 1193mm (2x54W T16) or 1493mm (2x80W) long. The same lighting level is obtained with up to 50 % less energy consumed and an exceptional luminaire efficiency of up to 100lm/W. A targeted range is available: two lengths of modules (1193 and 1493mm), four luminous flux options and two colour temperatures (3000K/5350lm-7000lm and 4000K/5450lm-7300lm) and three modes of electronic lighting management (non dimmable, dimmable Dali and Interactive-Dali System). Surf System Led is available in the same dimensions and is using the same finishing and fixing components like Surf System T16, guaranteeing perfect interchangeability with the fluorescent version. 1193 mm long module: Total luminous flux of luminaire: 5350 lm (3000 K) - 5450 lm (4000 K) Luminaire efficiency: 99 lm/W (3000 K) - 101 lm/W (4000 K) Light distribution: 100% indirect Total power of luminaire: 54W

TECHNICAL DRAWINGS



FEATURES

Article Code:	BD00001	Material:	Extruded Aluminium
Colour:	White	Series:	Indoor
Installation:	Wall, Suspension	Area contract:	Hospitality, null, Retail, Office
Environment:	Indoor	Emission:	Indirect

DIMENSIONS

Length:	cm 119	Glow Wire Test:	960
Width:	cm 18		
Height:	cm 3.2		
Weight:	kg 5.1		

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1		
Watt:	65W		
Type:	0		
Class:	A		

LUMINAIRE

Watt:	53W	Delivered lumens output (lm):	6223lm
Voltage:	220V-240V	CCT:	3000K
		Efficiency:	83%
		Efficacy:	117.42lm/W
		CRI:	80

Notes

ACCESSORIES


SURF TERMINALE
BCO
M090220



INTERACTIVE-DALI
kit Ø86mm, white,
recessed. Can be
connected to a
max. 11 DALI
dimmable units. Is
operated through
INTERACTIVE-DALI
remote control or
external push
button.
M074030



SURF ELEMENT DE
JONCTION + BLC
M090520



SURF ATTACCO A
PTE ALIM.BCO
M090920



.SURF ELEMENT
DE JONCTION T
BLC
M090420



SURF BASETTA
SOSP.BCO
M090620



Extension
movement
detector white,
recessed. To be
used when the
area to be covered
is bigger than
6,00x5,00m by
height 2,50m. To
be connected to
one of the outputs
of the
INTERACTIVE-DALI
controller. No
extra mains
connection
required.
M074130



SURF ATTACCO A
PARETE BCO
M090820



SURF SOSPENS.
ALIM.5 POLI BCO
M091820



SURF GIUNTO 90°
BCO
M090320



INTERACTIVE-DALI
remote control.
M104900



SURF BASETTA
SOSP.ALIM.BCO
M090720