PRODUCT DATA SHEET PRODUCT CODE: AB06156

# Tagora Ceiling 80 - Led 36° 3000K - Grey/White - Undimmable



**IP**20 ♠ ▼

#### **DESIGN BY**

S./R. Cornelissen


## **DESCRIPTION**

Series of ceiling mounted luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. 

\[
\textsuperscript{\textsuperscript{Aluminium body available in different two-coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. 

\[
\textsuperscript{\textsuperscript{Tagora 80 and 270 offer a high-output spot light with aluminium optics. 
\textsuperscript{Tagora 270 uses a proprietary system based \textsuperscript{on a hybrid combined lens and reflector optic. 
\textsuperscript{This system helps to create defined narrow beams using high-powered LED modules of large dimensions. 
\textsuperscript{Tagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. 
\textsuperscript{LED versions use high-output sources. 
\textsuperscript{Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. 
\textsuperscript{Only ceiling mounted installation allowed.} 
\textsuperscript{Compliant with standard EN60598-1 and other specific standards.} 
\]

## **TECHNICAL DRAWINGS**



FEATURES	,
----------	---

Article Code:	AB06156	Material:	Aluminium
Colour:	Grey/White	Series:	Indoor
Installation:	Ceiling		

## **DIMENSIONS**

Height:	cm 33	Cutout shape:	Rounded
Weight:	kg 1.1	Glow Wire Test:	960

## **INCLUDED SOURCES**

Category: Number:	LED 1	Color temperature (K): Color Tolerance:	3000K MacAdam 3SDCM
Watt:	14W	CRI:	90
Туре:	0	Service Life:	L70 (6K) 60000h
Class:	Α		

## **LUMINAIRE**

Power Supply:	220/240Vac 50/60Hz Delivered lum	ens output (lm):1027lm
	electronic hallast CCT	3000K

included	Efficiency:	69%	
Trasformer availability:	Integrated	Efficacy:	73.39Im/W
Watt:	14W	CRI:	90
Voltage:	220V-240V		