



Tagora Incasso 80 - Led 3000K - 44° - White



IP20 🕼 🤃 Dimmerable: +①-

TECHNICAL DRAWINGS



DESIGN BY

S./R. Cornelissen

DESCRIPTION

Series of ceiling mounted luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. Consists of a trimless recessed frame fitted into the ceiling and an optical unit with an aluminium body painted in a range of colours: beige/white, grey/white, black/orange, black/vert and black/blue. Tagora 80 and 270 offer a high-output spot light with aluminium optics. Dagora 270 uses a proprietary system based on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. DTagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use high-output sources. Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. Only ceiling recessed installation allowed. Compliant with standard EN60598-1 and other specific standards.

FEATURES			
Article Code: Colour: Installation:	AB00201 White Recessed	Material: Series:	Aluminium Indoor
DIMENSIONS			
Height: Weight: Recessed depth:	cm 15.4 kg 0.3 cm 17.5	Cutout diameter: Cutout shape: Glow Wire Test:	cm 9.2 Rounded 960
INCLUDED SOURCES			
Category: Number: Watt: Type: Class:	LED 1 14W 0 A	Color temperature (K): Color Tolerance: CRI: Service Life:	3000K MacAdam 3SDCM 90 L70 (6K) 60000h
LUMINAIRE			
Power Supply:	Power supply supplied separately	Delivered lumens output (lm) CCT:	: 1110lm 3000K
Trasformer availability: Watt: Voltage:	Remote 14W 220V-240V	Efficiency: Efficacy: CRI:	75% 79.34lm/W 90



ACCESSORIES

NO IMAGE AVAILABLE DRIVER cc 16W

350mA 220-240 156 52 26 1max DALI dimmable/Push dali M077401