
Tagora Suspension 570 - Direct + Indirect Emission - dimmable - Beige/White



PRODUCT DATA SHEET

TECHNICAL DRAWINGS



DESIGN BY

S./R. Cornelissen

DESCRIPTION

Voltage:

Series of suspended luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. DAluminium body available in different twocoloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. DSteel suspension cables allowing quick adjustment, 2 metre length. DTagora 80 and 270 offer a high-output spot light with aluminium optics. DTagora 270 uses a proprietary system basedDon a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. DTagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use highoutput sources. DIntegrated electronic power supply, dimmable or non-dimmable options, depending on the version. DCompliant with standard EN60598-1 and other specific standards.

FEATURES			
Article Code: Colour: Installation:	M240321 Beige/White Suspension	Material: Series:	Aluminium Indoor
DIMENSIONS			
Height: Weight: Base Diameter: Max Height from ceiling:	cm 19 kg 6.6 cm 18 cm 200	Glow Wire Test:	960°
INCLUDED SOURCES			
Category: Number: Watt: Type: Class:	LED 1 58W 0 A	Color temperature (K): Color Tolerance: CRI: Service Life:	4000K MacAdam 3SDCM 80 L70 (6K) 50000h
LUMINAIRE			
Power Supply:	220/240Vac 50/60H electronic ballast included	z Delivered lumens output (CCT: Efficiency:	(Im): 4944lm 4000K 45%
Watt:	72W	Efficacy:	64.10lm/W

CRI:

Dimmable Typology:

220V-240V

80

Dali