

Tagora Suspension 570 - Direct + Indirect Emission - dimmable - Black/Blue



Dimmerable: + 10-

DESIGN BY

S./R. Cornelissen

DESCRIPTION


Series of suspended luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. □Steel suspension cables allowing quick adjustment, 2 metre length.

[Tagora 80 and 270 offer a based I on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions.

☐ Tagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use highoutput sources. Integrated electronic power supply, dimmable or non-dimmable options, depending on the version.

©Compliant with standard EN60598-1 and other specific standards.

TECHNICAL DRAWINGS



FEATURES

| Article Code: | M240331 | Material: | Aluminium |
|---------------|------------|-----------|-----------|
| Colour: | Black/Blue | Series: | Indoor |
| Installation: | Suspension | | |

DIMENSIONS

| neight. | CIII 19 |
|--------------------------|---------|
| Weight: | kg 6.6 |
| Base Diameter: | cm 18 |
| Max Height from ceiling: | cm 200 |

INCLUDED SOURCES

| Category: | LED | Color temperature (K): | 4000K |
|-----------|-----|------------------------|-----------------|
| Number: | 1 | Color Tolerance: | MacAdam 3SDCM |
| Watt: | 58W | CRI: | 80 |
| Туре: | 0 | Service Life: | L70 (6K) 50000h |
| Class: | Α | | |

Glow Wire Test:

960°

Dali

LUMINAIRE

| Power Supply: | 220/240Vac 50/60Hz Delivered lumens output (lm):4944lm | | | |
|---------------|--|-------------|-----------|--|
| | electronic ballast | сст: | 4000K | |
| | included | Efficiency: | 45% | |
| Watt: | 72W | Efficacy: | 64.10lm/W | |
| Voltage: | 220V-240V | CRI: | 80 | |