
Tagora Suspension 570 - Direct + Indirect Emission - dimmable - Gray/White



TECHNICAL DRAWINGS



DESIGN BY

S./R. Cornelissen

DESCRIPTION

Voltage:

Series of suspended luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. DAluminium body available in different twocoloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. []Steel suspension cables allowing quick adjustment, 2 metre length. DTagora 80 and 270 offer a high-output spot light with aluminium optics. ITagora 270 uses a proprietary system based I on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. DTagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use highoutput sources. Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. Compliant with standard EN60598-1 and other specific standards.

| FEATURES | | | |
|--|---|---|---|
| Article Code: Colour: Installation: | M240261 Gray/White Suspension | Material: Series: | Aluminium Indoor |
| DIMENSIONS | | | |
| Height: Weight: Base Diameter: Max Height from ceiling: | cm 19 kg 6.6 cm 18 cm 200 | Glow Wire Test: | 960° |
| INCLUDED SOURCES | | | |
| Category: Number: Watt: Type: Class: | LED 1 58W 0 A | Color temperature (K): Color Tolerance: CRI: Service Life: | 3000K MacAdam 3SDCM 80 L70 (6K) 50000h |
| LUMINAIRE | | | |
| Power Supply: | 220/240Vac 50/60H electronic ballast included | z Delivered lumens output (CCT: Efficiency: | lm): 4675lm 3000K 45% |
| Watt: | 72W | Efficacy: | 59.94lm/W |

CRI:

Dimmable Typology:

220V-240V

80

Dali