960°



# Tagora Suspension 570 - Direct + Indirect Emission - dimmable - Gray/White



Dimmerable: + 10-

#### **DESIGN BY**

S./R. Cornelissen

### **DESCRIPTION**


Series of suspended luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. □Steel suspension cables allowing quick adjustment, 2 metre length. 

[Tagora 80 and 270 offer a based I on a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. 

☐ Tagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use highoutput sources. Integrated electronic power supply, dimmable or non-dimmable options, depending on the version. 

©Compliant with standard EN60598-1 and other specific standards.

### **TECHNICAL DRAWINGS**



### **FEATURES**

| Article Code: | M240361    | Material: | Aluminium |
|---------------|------------|-----------|-----------|
| Colour:       | Gray/White | Series:   | Indoor    |
| Installation: | Suspension |           |           |

#### **DIMENSIONS**

| Height:                  | cm 19  | Glow Wire Test: |
|--------------------------|--------|-----------------|
| Weight:                  | kg 6.6 |                 |
| Base Diameter:           | cm 18  |                 |
| Max Height from ceiling: | cm 200 |                 |

## **INCLUDED SOURCES**

| Category: | LED | Color temperature (K): | 4000K           |
|-----------|-----|------------------------|-----------------|
| Number:   | 1   | Color Tolerance:       | MacAdam 3SDCM   |
| Watt:     | 58W | CRI:                   | 80              |
| Туре:     | 0   | Service Life:          | L70 (6K) 50000h |
| Class:    | Α   |                        |                 |

## **LUMINAIRE**

| Power Supply: | 220/240Vac 50/60Hz <b>Delivered lumens output (lm):</b> 4944lm |            |                |
|---------------|--|------------|----------------|
|               | electronic ballast   | сст:       | 4000K          |
|               | included   | Efficiency | <b>4 □ 0 6</b> |

Efficacy: 64.10lm/W Watt: 72W Voltage: 220V-240V **Dimmable Typology:** Dali