PRODUCT DATA SHEET PRODUCT CODE: AB02552

# Tagora Suspension 80 - Led 44° 4000K - Beige/White - Undimmable



**IP**20 ⊕ ₹


#### **DESIGN BY**

S./R. Cornelissen

### **DESCRIPTION**

Series of suspended luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. \( \text{DAluminium body available in different two-coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. \( \text{DSteel suspension cables allowing quick adjustment, 2 metre length. } \text{DTagora 80 and 270 offer a high-output spot light with aluminium optics. } \( \text{DTagora 270 uses a proprietary system based} \text{Don a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. } \( \text{DTagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use highoutput sources. } \( \text{DIntegrated electronic power supply, dimmable or non-dimmable options, depending on the version. } \( \text{DCompliant with standard EN60598-1 and other specific standards.} \)

### **TECHNICAL DRAWINGS**



### **FEATURES**

| Article Code: | AB02552     | Material: | Aluminium |
|---------------|-------------|-----------|-----------|
| Colour:       | Beige/White | Series:   | Indoor    |
| Installation: | Suspension  |           |           |

**Glow Wire Test:** 

960

#### **DIMENSIONS**

| neignt:                  | CIII 55 |
|--------------------------|---------|
| Weight:                  | kg 1.1  |
| Base Diameter:           | cm 10   |
| Max Height from ceiling: | cm 200  |

## **INCLUDED SOURCES**

| Category: | LED | Color temperature (K): | 4000K           |
|-----------|-----|------------------------|-----------------|
| Number:   | 1   | Color Tolerance:       | MacAdam 3SDCM   |
| Watt:     | 14W | CRI:                   | 90              |
| Туре:     | 0   | Service Life:          | L70 (6K) 60000h |
| Class:    | Α   |                        |                 |

## **LUMINAIRE**

Voltage:

| Power Supply:            | 220/240Vac 50/60Hz <b>Delivered lumens output (lm):</b> 1145lm |             |           |
|--------------------------|--|-------------|-----------|
|                          | electronic ballast   | CCT:        | 4000K     |
|                          | included   | Efficiency: | 75%       |
| Trasformer availability: | Integrated   | Efficacy:   | 81.80lm/W |
| Watt:                    | 14W  | CRI:        | 90        |

220V-240V