PRODUCT DATA SHEET

Tagora Suspension 970 - Direct + Indirect Emission - dimmable - Black/Blue




DESIGN BY

S./R. Cornelissen

DESCRIPTION

Series of suspended luminaires available in 4 diameters (80 mm, 270 mm, 570 mm, 970 mm), using high-output LEDs, Retrofit LEDs. \(\text{DAluminium body available in different two-coloured versions: beige/white, grey/white, black/orange, black/vert and black/blue. \(\text{DSteel suspension cables allowing quick adjustment, 2 metre length. } \text{DTagora 80 and 270 offer a high-output spot light with aluminium optics. } \(\text{DTagora 270 uses a proprietary system based} \text{Don a hybrid combined lens and reflector optic. This system helps to create defined narrow beams using high-powered LED modules of large dimensions. } \(\text{DTagora 570 and 970 come with a PMMA diffuser, offering a comfortable diffused light. LED versions use highoutput sources. } \(\text{DIntegrated electronic power supply, dimmable or non-dimmable options, depending on the version. } \(\text{DCompliant with standard EN60598-1 and other specific standards.} \)

TECHNICAL DRAWINGS



FEATURES

Article Code:	M250831	Material:	Aluminium
Colour:	Black/Blue	Series:	Indoor
Installation:	Suspension		

DIMENSIONS

Height:	cm 23	Glow Wire Test:	960°
Weight:	kg 21		

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 3SDCM
Watt:	11W	CRI:	80
Type:	2	Service Life:	L70 (6K) 50000h
Class:	Α		
Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 3SDCM
Watt:	84W	CRI:	80
Type:	0	Service Life:	L70 (6K) 50000h
Class:	Α		

LUMINAIRE

Power Supply:	220/240Vac 50/60Hz Delivered lumens output (lm):7536lm		
	electronic ballast	CCT:	3000K

 included
 Efficiency:
 52%

 Watt:
 95W
 Efficacy:
 56.80lm/W

 Voltage:
 220V-240V
 CRI:
 80

 Dimmable Typology:
 Dali