PRODUCT DATA SHEET PRODUCT CODE: AP52118

# Vector Recessed 40 - 8W 13° 2700K Brushed copper



**IP**20


#### **DESIGN BY**

Carlotta de Bevilacqua

#### **DESCRIPTION**

Two sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom. Vector 40 and 55 available version: recessed trim or trimless.

#### **TECHNICAL DRAWINGS**



#### **FEATURES**

Inclination:

**Rotation:** 

| Article Code: Colour: Installation: Environment: DIMENSIONS | AP52118<br>Brushed copper<br>Projector, Recessed<br>Indoor | Material:<br>Series: | Alluminium body<br>Indoor, 2018<br>Artemide Collection |
|---|--|----------------------|--|
| Height:   | cm 10.9  | Cutout diameter:     | cm 8.6   |

-90+90

cm 360

# **INCLUDED SOURCES**

| Category: | LED | Color temperature (K): | 2700K           |
|-----------|-----|------------------------|-----------------|
| Number:   | 1   | Color Tolerance:       | MacAdam 3SDCM   |
| Watt:     | 8W  | CRI:                   | 90              |
| Type:     | 0   | Service Life:          | L70 (6K) 50000h |
|           |     |                        |                 |

| 8W | Delivered lumens output (lm): 505lm |                                  |  |
|----|-------------------------------------|----------------------------------|--|
|    | CCT:                                | 2700K                            |  |
|    | Efficiency:                         | 81%                              |  |
|    | Efficacy:                           | 63.16lm/W                        |  |
|    | CRI:                                | 90                               |  |
|    | 8W                                  | CCT:<br>Efficiency:<br>Efficacy: |  |

## Notes

Trimless recessed structure not included, to be ordered separately. Driver 700/500mA SELV supplied separately. Depending on the driver, the product can be dimmable DALI or undimmable.



### **ACCESSORIES**



Driver 15-32W 500-700mA - 220-24Vac -Undimmable -146,5x43,5x22 mm (LxWxH) dv1030



Vector 40 -Optional Trim Frame Ø 108 -Black Ap59004



Driver 11-25W 500-700mA - 220-24Vac - Dimmable DALI -164x38x24,5 mm (LxWxH) dv1031



Vector 40 -Trimless recessed structure AP50000



Vector 40 -Optional Trim Frame Ø 108 -White Ap59001