PRODUCT DATA SHEET PRODUCT CODE: AP56320

# Vector Recessed 55 - 17,5W 32° 4000K Brushed Bronze



**IP**20 🕼


#### **DESIGN BY**

Carlotta de Bevilacqua

#### **DESCRIPTION**

Two sizes with three different beam angles each (spot, flood, wide flood) obtained by means of refractive or hybrid optical units. The junction allows 360° rotation and 90° tilting for maximum emission adjustment freedom. Vector 40 and 55 available version: recessed trim or trimless.

### **TECHNICAL DRAWINGS**



## **FEATURES**

**Rotation:** 

| Article Code: Colour: Installation: Environment: DIMENSIONS | AP56320<br>Brushed Bronze<br>Projector, Recessed<br>Indoor | Material:<br>Series: | Alluminium body<br>Indoor, 2018<br>Artemide Collection |
|-------------------------------------------------------------|------------------------------------------------------------|----------------------|--------------------------------------------------------|
| Height:                                                     | cm 13.6                                                    | Cutout diameter:     | cm 8.6                                                 |
| Inclination:                                                | -90+90                                                     |                      |                                                        |

cm 360

## **INCLUDED SOURCES**

| Category: | LED   | Color temperature (K): | 4000K           |
|-----------|-------|------------------------|-----------------|
| Number:   | 1     | Color Tolerance:       | MacAdam 3SDCM   |
| Watt:     | 17,5W | CRI:                   | 90              |
| Туре:     | 0     | Service Life:          | L70 (6K) 50000h |
|           |       |                        |                 |

| LUMINAIRE |       |                                      |           |  |
|-----------|-------|--------------------------------------|-----------|--|
| Watt:     | 17,5W | Delivered lumens output (lm): 1356lm |           |  |
|           |       | CCT:                                 | 4000K     |  |
|           |       | Efficiency:                          | 68%       |  |
|           |       | Efficacy:                            | 79.79lm/W |  |
|           |       | CRI:                                 | 90        |  |
|           |       |                                      |           |  |

# **Notes**

 $Trimless\ recessed\ structure\ not\ included,\ to\ be\ ordered\ separately.\ Driver\ 700/500mA\ SELV\ supplied\ separately.\ Depending\ on\ the\ driver,\ the\ product\ can\ be\ dimmable\ DALI\ or\ undimmable.$ 



## PRODUCT DATA SHEET

### **ACCESSORIES**



Driver 15-32W 500-700mA - 220-24Vac -Undimmable -146,5x43,5x22 mm (LxWxH) dv1030



Vector 55 -Optional Trim Frame Ø 108 -Black Ap59104



Driver 11-25W 500-700mA - 220-24Vac - Dimmable DALI -164x38x24,5 mm (LxWxH) dv1031



Vector 40 -Trimless recessed structure AP50000



Vector 55 -Optional Trim Frame Ø 108 -White Ap59101