

**BEGA****31 415**

Wall luminaire »Brügge«



Project · Reference number

Date

## Product data sheet

### Application

Wall luminaire for many lighting tasks on or in buildings.

The hand-blown crystal bubble glass of this luminaire is distinguished by the very lively surface.

Thus the light is distributed in many directions.

### Product description

Luminaire made of aluminium alloy and stainless steel

BEGA Unidure® coating technology

Crystal bubble glass

2 mounting holes  $\varnothing$  5.2 mm

Distance apart 70 mm

1 cable entry for mains supply cable

up to  $\varnothing$  10,5 mm max.  $3 \times 1,5^{\square}$

Connecting terminal  $2,5^{\square}$

with plug connection

Earth conductor connection


Lampholder E 27


Safety class I

Protection class IP 44

Protected against granular foreign bodies

> 1 mm and splash water

 – Safety mark

 – Conformity mark

Weight: 3.3 kg

### Lamp

Luminaire with lampholder E 27

Lamp output max. 100 W

For this luminaire we recommend the following BEGA LED lamps:

**13 509** LED 7 W · 805 lm · 2700 K

**13 547** LED 7 W · 805 lm · 2700 K  
dimnable

**13 583** LED 7 W · 805 lm · 3000 K

**13 585** LED 7 W · 805 lm · 3000 K  
dimnable

**13 511** LED 8 W · 1055 lm · 2700 K

**13 562** LED 12 W · 1520 lm · 2700 K

**13 563** LED 12 W · 1520 lm · 2700 K  
dimnable

**13 587** LED 8 W · 1055 lm · 3000 K

**13 589** LED 12 W · 1520 lm · 3000 K

**13 591** LED 12 W · 1520 lm · 3000 K  
dimnable

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.

