BEGA

Pendant luminaire for indoor use

Project · Reference number

Product data sheet

Application

Pendant luminaire · indoor luminaire for freeradiating and uniform light with hand-blown opal glass, satin matt and metal housing.

Product description

Stainless steel fitter and canopy Hand-blown opal glass, satin matt Black flex suspension 3×0.75 ^o with 1 steel messenger wire Overall length of luminaire approx. 1950 mm Connection terminal 2.5° Earth conductor connection Lampholder E 27 Safety class I **C** ϵ – Conformity mark Weight: 1.4 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamps

Luminaire with lampholder E 27 Lamp output max. 60 W

For this luminaire we recommend the following BEGA LED lamps:

 13510
 LED 7 W · 805 lm · 2700 K

 13548
 LED 7 W · 805 lm · 2700 K

 dimmable

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.

Article No. 45 485.2

Optional finishes

- White enamel
- Stainless steel code number .2
- ChromeBrass

code number **.3** code number **.4**

Date



