BEGA 45 488.3

Pendant luminaire for indoor use

Project · Reference number

Date

Product data sheet

Application

Pendant luminaire \cdot indoor luminaire for freeradiating and uniform light with hand-blown opal glass, satin matt and metal housing.

Product description

Metal housing and canopy, chrome finish Hand-blown opal glass, satin matt Black flex suspension 3×0.75 $^{\square}$ with 1 steel messenger wire Overall length of luminaire approx. 2000 mm Connecting terminals 2.5 $^{\square}$ Earth conductor connection Lampholder E 27 Safety class I

C € – Conformity mark Weight: 2.9 kg

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Lamps

Luminaire with lampholder E 27 Lamp output max. 200 W

For this luminaire we recommend the following BEGA LED lamps:

13510 LED 7 W ⋅ 805 lm ⋅ 2700 K 13548 LED 7 W ⋅ 805 lm ⋅ 2700 K dimmable 13512 LED 8 W ⋅ 1055 lm ⋅ 2700 K 13564 LED 12 W ⋅ 1400 lm ⋅ 2700 K 13565 LED 12 W ⋅ 1400 lm ⋅ 2700 K dimmable

Detailed technical and lighting data for the lamps can be found in the data sheets on our website.

Article No. 45 488.3

Optional finishes

White enamel
Stainless steel
Chrome
Brass
code number .2
code number .3
code number .4

If the article number is followed by a **P**, we can also supply these luminaires in impact-resistant synthetic material.



