

**BEGA****50 033**

Ceiling and wall luminaire for indoor use



Project · Reference number

Date

## Product data sheet

### Application

Ceiling and wall luminaire · indoor luminaire made of hand-blown opal glass and metal housing, for all lighting tasks. They are ideal for places where a soft and uniform lighting distribution is required.

### Product description

Metal housing,  
finish white enamel  
Hand-blown opal glass, satin matt,  
with bayonet closure  
2 mounting holes  $\varnothing$  6 mm  
Distance apart 340 mm  
2 cable entries for through-wiring for mains  
cable up to  $\varnothing$  10,5 mm max.  $3 \times 1.5^{\square}$   
Connection terminal  $2.5^{\square}$   
Earth conductor connection  
LED power supply unit  
220-240 V  $\sim$  0/50-60 Hz  
DC 170-280 V  
Safety class I  
 – Safety mark  
**CE** – Conformity mark  
Weight: 4.6 kg

### Inrush current

Inrush current: 5 A / 50  $\mu$ s  
Maximum number of luminaires of this  
type per miniature circuit breaker:  
B10A: 31 luminaires  
B16A: 50 luminaires  
C10A: 52 luminaires  
C16A: 85 luminaires

### Lamp

Module connected wattage 28.1 W  
Luminaire connected wattage 32.5 W  
Rated temperature  $t_a = 25^{\circ}\text{C}$   
Ambient temperature  $t_{a\text{max}} = 35^{\circ}\text{C}$

### 50 033 K3


Colour temperature 3000 K  
Colour rendering index CRI > 90  
Module luminous flux 3685 lm  
Luminaire luminous flux 2416 lm  
Luminaire luminous efficiency 74,3 lm/W

### 50 033 K2

Colour temperature 2700 K  
Colour rendering index CRI > 90  
Module luminous flux 3655 lm  
Luminaire luminous flux 2396 lm  
Luminaire luminous efficiency 73,7 lm/W

### 50 033 K4

Colour temperature 4000 K  
Colour rendering index CRI > 80  
Module luminous flux 3820 lm  
Luminaire luminous flux 2504 lm  
Luminaire luminous efficiency 77 lm/W



### Service life of the LED

Ambient temperature  $t_a = 25^{\circ}\text{C}$   
– at 302,000h: L70B50  
max. ambient temperature  $t_a = 35^{\circ}\text{C}$   
– at 164,000h: L70B50

### Light technique

Luminaire data for the light planning program  
DIALux for outdoor lighting, street lighting and  
indoor lighting as well as luminaire data in  
EULUMDAT- and IES-format you will find on the  
BEGA web page [www.bega.com](http://www.bega.com).

### Article No. 50 033

LED colour temperature optionally 2700 K,  
3000 K or 4000 K  
2700 K – Article number + **K2**  
3000 K – Article number + **K3**  
4000 K – Article number + **K4**

If the article number is followed by a **P**, we can  
also supply these luminaires in impact-resistant  
synthetic material.

### Accessory · Trim rings

For this luminaire metal trim rings in 3 enamel  
surfaces are optional available.  
Trim rings are accessories and must be ordered  
separately.

Item	Part. No
Finish enamel <b>white</b>	<b>13007</b>
Finish enamel <b>palladium</b>	<b>13008</b>
Finish enamel <b>glossy silver</b>	<b>13009</b>