

BEGA**50 047 P**

Ceiling and wall luminaire for indoor use

Project · Reference number

Date

Product data sheet**Application**

Ceiling and wall luminaire · indoor luminaire made of impact resistant synthetic diffuser and metal housing, for all lighting tasks. They are ideal for places where a soft and uniform lighting distribution is required.

Luminaire with group module (Slave).

If several luminaires with group module (Slave) are to be networked together, the additional use of a luminaire with group module and HF-motion sensor (Master) is compulsory.

Product description

Metal housing,
finish white enamel
Impact resistant synthetic diffuser, white,
with bayonet closure
Integrated group module,
maximum range 30 m
2 mounting holes \varnothing 5.5 mm
Distance apart 230 mm
2 cable entries for through-wiring for mains
cable up to \varnothing 10.5 mm max. 3×1.5^2
Connection terminal 2.5^2
Earth conductor connection
LED power supply unit
230 V \sim 50 Hz
Safety class I
CE – Conformity mark

Lamp

Module connected wattage 16.8 W
Luminaire connected wattage 21.4 W
Rated temperature $t_a = 25 \text{ }^\circ\text{C}$
Ambient temperature $t_{a \text{ max}} = 30 \text{ }^\circ\text{C}$

50 047 P K3


Colour temperature 3000 K
Colour rendering index CRI > 90
Module luminous flux 2110 lm
Luminaire luminous flux 1874 lm
Luminaire luminous efficiency 87,6 lm/W

50 047 P K2

Colour temperature 2700 K
Colour rendering index CRI > 90
Module luminous flux 2095 lm
Luminaire luminous flux 1860 lm
Luminaire luminous efficiency 86,9 lm/W

50 047 P K4

Colour temperature 4000 K
Colour rendering index CRI > 90
Module luminous flux 2185 lm
Luminaire luminous flux 1940 lm
Luminaire luminous efficiency 90,7 lm/W

**Service life of the LED**

Ambient temperature $t_a = 25 \text{ }^\circ\text{C}$
– at 157,000h: L70B50

max. ambient temperature $t_a = 30 \text{ }^\circ\text{C}$
– at 118,000h: L70B50

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Article No. 50 047 P

LED colour temperature optionally 2700 K, 3000 K or 4000 K
2700 K – Article number + **K2**
3000 K – Article number + **K3**
4000 K – Article number + **K4**

Accessory · Trim rings

For this luminaire metal trim rings in 3 enamel surfaces are optional available. Trim rings are accessories and must be ordered separately.

	Part. No
Finish enamel white	13 004
Finish enamel palladium	13 005
Finish enamel glossy silver	13 006