

**BEGA****50 066.2**

Wall luminaire for indoor use



Project · Reference number

Date

## Product data sheet

### Application

Free-radiating wall luminaire · indoor luminaire  
made of hand-blown opal glass, satin matt and  
metal housing, for all lighting tasks.

### Product description

Metal housing  
stainless steel finish  
Hand-blown opal glass, satin matt  
2 mounting holes  $\varnothing$  5 mm  
Distance apart 115 x 55 mm  
Connecting terminals 2.5<sup>□</sup>  
Earth conductor connection  
Installation surface 145 x 86 mm  
LED-Module for mains voltage  
220-230 V  $\sim$  50/60 Hz  
Safety class I  
 – Safety mark  
 – Conformity mark  
Weight: 1.0 kg

### Light technique

Luminaire data for the light planning program  
DIALux for outdoor lighting, street lighting and  
indoor lighting as well as luminaire data in  
EULUMDAT- and IES-format you will find on the  
BEGA web page [www.bega.com](http://www.bega.com).

### Lamp

Luminaire connected wattage	12 W
Rated temperature	$t_a = 25$ °C
Ambient temperature	$t_{a \text{ max}} = 40$ °C
Service life criteria	50 000 h / L <sub>70</sub>

### 50 066.2 K3

Module designation	LED-0607/830
Colour temperature	3000 K
Colour rendering index	$R_a > 80$
Module luminous flux	1080 lm
Luminaire luminous flux	979 lm
Luminaire luminous efficiency	81,6 lm/W

