

BEGA**50 519.2**

Ceiling luminaire for indoor use



Project · Reference number


Date

Product data sheet

Application

LED ceiling luminaire · indoor luminaire with direct and indirect light distribution.

Product description

Aluminium alloy housing,
stainless steel finish
Hand-blown opal glass,
satin matt, with screw neck
Reflector made of pure anodised aluminium
2 mounting holes \varnothing 4.5 mm
Distance apart 112 mm
The luminaire is suitable for through-wiring.
Connecting terminals 2.5[□]
Earth conductor connection
LED power supply unit
220-240 V \sim 0/50-60 Hz
DALI controllable
A basic isolation exists between power cable
and control line
Safety class I
 – Safety mark
CE – Conformity mark
Weight: 1.7 kg

Inrush current

Inrush current: 5 A / 50 μ s
Maximum number of luminaires of this
type per miniature circuit breaker:
B 10A: 31 luminaires
B 16A: 50 luminaires
C 10A: 52 luminaires
C 16A: 85 luminaires

Lamp


Module connected wattage	11.5 W
Luminaire connected wattage	13.7 W
Rated temperature	$t_a = 25$ °C
Ambient temperature	$t_{a \max} = 30$ °C

50 519.2 K3

Module designation	LED-0800/930
Colour temperature	3000 K
Colour rendering index	CRI > 90
Module luminous flux	1735 lm
Luminaire luminous flux	1210 lm
Luminaire luminous efficiency	88,3 lm/W

50 519.2 K4

Module designation	LED-0800/940
Colour temperature	4000 K
Colour rendering index	CRI > 90
Module luminous flux	1760 lm
Luminaire luminous flux	1227 lm
Luminaire luminous efficiency	89,6 lm/W



Service life of the LED

Ambient temperature $t_a = 25$ °C
– at 390,000h: L70B50
max. ambient temperature $t_a = 30$ °C
– at 370,000h: L70B50

Light technique

Direct and indirect light distribution.
Half beam angle 50°
Luminaire data for the light planning program
DIALux for outdoor lighting, street lighting and
indoor lighting, as well as luminaire data in
EULUMDAT and IES format are available on the
BEGA website at www.bega.com.

Article No. 50 519.2

LED colour temperature optionally 3000 K
or 4000 K
3000 K – Article number + **K3**
4000 K – Article number + **K4**

Finish options

- Enamel, velvet white Code number **.1**
- Stainless steel Code number **.2**
- Enamel, velvet black Code number **.5**