

Project · Reference number

Date

Product data sheet**Application**

Ceiling and wall luminaire · indoor luminaire made of impact resistant synthetic diffuser and metal housing, for all lighting tasks. They are ideal for places where a soft and uniform lighting distribution is required.

Product description

Metal housing,
finish white enamel
Impact resistant synthetic diffuser, white,
with sliding-bolt closure
2 mounting holes \varnothing 5.5 mm
Distance apart 200 mm
2 cable entries for through-wiring for mains
cable up to \varnothing 10.5 mm max. 3×1.5^2
Connecting terminal 2.5^2
with plug connection
Earth conductor connection
LED power supply unit
220-240 V \sim 0/50-60 Hz
DC 176-280 V
Safety class I
Protection class IP 44
Protected against granular foreign bodies
> 1 mm and splash water
CE – Conformity mark

Inrush current

Inrush current: 5 A / 50 μ s
Maximum number of luminaires of this
type per miniature circuit breaker:
B10A: 31 luminaires
B16A: 50 luminaires
C10A: 52 luminaires
C16A: 85 luminaires

Lamp

Module connected wattage 16.4 W
Luminaire connected wattage 18.2 W
Rated temperature $t_a = 25$ °C
Ambient temperature $t_{a \max} = 30$ °C


50 651 P K3

Module designation LED-0569/930
Colour temperature 3000 K
Colour rendering index CRI > 90
Module luminous flux 2050 lm
Luminaire luminous flux* 1760 lm
Luminaire luminous efficiency* 96,7 lm/W

50 651 P K4

Module designation LED-0569/940
Colour temperature 4000 K
Colour rendering index CRI > 90
Module luminous flux 2125 lm
Luminaire luminous flux* 1822 lm
Luminaire luminous efficiency* 100,1 lm/W

* preliminary data

**Lifetime of the LED**

Ambient temperature $t_a = 25$ °C
– at 259,000h: L70B50

max. ambient temperature $t_a = 30$ °C
– at 190,000h: L70B50

Light technique

Luminaire data for the light planning program
DIALux for outdoor lighting, street lighting and
indoor lighting as well as luminaire data in
EULUMDAT- and IES-format you will find on the
BEGA web page www.bega.com.

Article No. 50 651 P

LED colour temperature optionally 3000K
or 4000K
3000 K – Article number + **K3**
4000 K – Article number + **K4**