

**BEGA****56 341.3**

Pendant luminaire for indoor use



Project · Reference number



Date

## Product data sheet

### Application

Pendant luminaire · indoor luminaire for free-radiating and uniform light with hand-blown opal glass, satin matt and metal housing.

### Product description

Metal housing and canopy, chrome finish  
 Hand-blown opal glass, satin matt  
 Black flex suspension  $3 \times 0.75$  □  
 with 1 steel messenger wire  
 Overall length of luminaire ~2000 mm  
 Connecting terminals and earth conductor terminal 2,5<sup>□</sup>  
 Lampholder GX 24 q-3  
 Electronic ballast (EEI=A2)  
 220-240 V  $\sim$  0/50-60 Hz  
 DC 176-264 V  
 DC Start  $\geq 198$  V  
 Safety class I  
 – Safety mark  
 – Conformity mark  
 Weight: 1.5 kg

### Lamp

Compact fluorescent lamp  
 TC-TELI 26 W · GX 24 q-3

Osram: Dulux T/E Plus 26 W /... 1800 lm  
 Philips: PL-T TOP 26 W / 4p 1800 lm

Please note the lamp manufacturers' operating instructions.

### Article No. 56 341.3

Finish options

- Enamel, white
- Chrome

Code number **.1**

Code number **.3**

