

**BEGA****56 475**

Pendant luminaire for indoor use

Project · Reference number

Date

**Product data sheet****Application**

Pendant luminaire · indoor luminaire for free-radiating and uniform light with hand-blown opal glass and metal housing.

**Product description**

Metal housing and canopy  
 White enamel finish  
 Hand-blown opal glass  
 White flex suspension  $5 \times 0,7$  □  
 with 1 steel messenger wire  
 Overall length of luminaire approx. 4000 mm  
 Connection terminal 2.5 □  
 Earth conductor connection  
 2-pole connecting terminal for digital control  
 Lampholder 2 G 11  
 Electronic ballast  
 DALI controllable  
 A basic isolation exists between power cable and control line  
 220-240 V  $\sim$  0/50-60 Hz  
 Safety class I  
**CE** – Conformity mark  
 Weight: 4.9 kg

**Light technique**

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page [www.bega.com](http://www.bega.com).

**Lamps**

2 Compact fluorescent lamps  
 TC-L 40 W · 2 G 11

Osram: Dulux L 40 W 3500 lm  
 Philips: PL-L 40 W / 4p 3500 lm

Please note the lamp manufacturers' operating instructions.

