

GLASHÜTTE LIMBURG**Product data sheet****Pendant luminaire****5567.3**

Project · Reference number

Date

Application

Pendant luminaire for free-radiating and uniform light made of hand-blown opal glass, satin matt. Metal luminaire housing.
The used LED technique offers durability and optimal light output with low power consumption at the same time.

Product description

Metal luminaire housing,
finish polished aluminium
Hand-blown opal glass,
satin matt, with screw neck
Black flex suspension $2 \times 0,5 \square$
with 1 steel messenger wire
Overall length of luminaire ~2000 mm
LED power supply unit inside canopy
220-240 V \sim 0/50-60 Hz
DALI controllable
Safety class I
CE – Conformity mark
Weight: 2.5 kg

Lamp

Module connected wattage	19 W
Luminaire connected wattage	23 W
Rated temperature	$t_a = 25 \text{ }^\circ\text{C}$
Service life criteria	50 000 h/L ₇₀

5567.3

Module designation	LED-0328/830
Colour temperature	3000 K
Colour rendering index	$R_a > 80$
Module luminous flux	2210 lm
Luminaire luminous flux	1627 lm
Luminaire luminous efficiency	70,7 lm/W

www.glashuette-limborg.com**5567.3 K4**

Module designation	LED-0328/840
Colour temperature	4000 K
Colour rendering index	$R_a > 80$
Module luminous flux	2375 lm
Luminaire luminous flux	1748 lm
Luminaire luminous efficiency	76 lm/W

Article No. 5567.3

Finish options

- Enamel, white
- Stainless steel
- Polished aluminium

Code number .1
Code number .2
Code number .3

Colour temperature 3000 K.

Also available with 4000 K on request.

3000 K – article number

4000 K – article number + **K4**