

#### THE BLACK LINE NO TRIM 2 SPOTS

Number of heads

**Mounting** Ceiling recessed

Lamps descriptionPower LED 6,5W 2 x 197 lm 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

**Environment** Indoor

**Notes** No Trim version can be connected in a continuous line.

### **OPTICAL**

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle II° Spot

#### **ELECTRICAL**

Transformer availability
Separate item
Transformer mounting
Remote
Transformer type
Electronic
Emergency
Insulation class
Class III

#### **PHYSICAL**

Length (mm) 190 Recessed depth (mm) 71

Construction material Extruded aluminum

Weight (kg) 0,74






The Black Line No Trim 2 Spots designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. 1050 mA remote power supply not included.





## CERTIFICATIONS











Flos.architectural@flos.com www.flos.com



## The Black Line No Trim 2 Spots . Accessories

#### **Power Supply**







#### **Constant Current Power** Supply for LED. 25-50W

Continuous current power supply of 25-50W, 220/240V - 50/60Hz with power current selected through adjustable 350/500/550/650/700/750/850/ 900/1050mA Dali switch, I-10V switch or push dimming.

Maximum lenght of 1.5 mm2 secundary conductor (m): 10

Maximum lenght of 2.5 mm2 secundary conductor (m): 15



# Constant Current Power Supply for LED. 22W / 1050 mA Non dimmable continuous current power supply 220/240V - 50/60Hz. (110V = 12W)

Maximum lenght of 1.5 mm2 secundary conductor (m): 20

Maximum lenght of 2.5 mm2 secundary conductor (m): 30



The Black Line No Trim 2 Spots . Lamps



**Power LED** 

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




#### The Black Line No Trim 2 Spots designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. 1050 mA remote power supply not included.



03.0051.14.ANT - 341lm Black



#### **CERTIFICATIONS**













Flos.architectural@flos.com www.flos.com