

THE BLACK LINE NO TRIM 8 SPOTS

Number of heads

Mounting Ceiling recessed

Lamps descriptionPower LED 26W 8 x 197 lm 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes No Trim version can be connected in a continuous line.

OPTICAL

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 42° Flood

ELECTRICAL


Transformer availability
Separate item
Transformer mounting
Remote
Transformer type
Electronic
Emergency
Insulation class
Class III

PHYSICAL

Length (mm) 670 Recessed depth (mm) 71

Construction material Extruded aluminum

Weight (kg) 2,34






The Black Line No Trim 8 Spots designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. 1050 mA remote power supply not included.





CERTIFICATIONS











Flos.architectural@flos.com www.flos.com



The Black Line No Trim 8 Spots . Accessories

Power Supply









60.8530

Constant Current Power Supply for LED. 25-50W

Continuous current power supply of 25-50W, 220/240V - 50/60Hz with power current selected through adjustable 350/500/550/650/700/750/850/900/1050mA Dali switch, I-10V switch or push dimming.

Maximum lenght of 1.5 mm2 secundary conductor (m): 10

Maximum lenght of 2.5 mm2 secundary conductor (m): 15

60.8548

Constant Current Power Supply for LED. 24/33W

Continuous current power supply of 24/33W, 220/240V - 50/60Hz with power current selected through adjustable 500/1050 mA.

Maximum lenght of 1.5 mm2 secundary conductor (m): 20

Maximum lenght of 2.5 mm2 secundary conductor (m): 30

60.9276

Continuous current power supply of 20-40W

Continuous current power supply of 20-40W, 110/240V - 50/60Hz with power current selected through adjustable 350/400/500/550/600/650/700/750/-800/850/900/950 mA Dali switch, 1-10V switch or push dimming.

Maximum lenght of 1.5 mm2 secundary conductor (m): 10

Maximum lenght of 2.5 mm2 secundary conductor (m): 15




The Black Line No Trim 8 Spots designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. 1050 mA remote power supply not included.



03.0061.14.ANT - 1252lm Black



670

The Black Line No Trim 8 Spots . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED

CERTIFICATIONS













Flos.architectural@flos.com www.flos.com