

EASY KAP Ø80 FIXED OPTIC MEDIUM

| | |
|-------------------------|--|
| Number of heads | 1 |
| Mounting | Ceiling recessed |
| Lamps description | LED Array DC 500 mA 9,2W 698 lm 2700K CRI 90 |
| Luminaire luminous flux | Extreme Cut-off. See reference number |
| Environment | Indoor |
| Notes | Diffusing lens included |

OPTICAL

| | |
|-----------------------------|-----------|
| Aiming | Fixed |
| Light distribution symmetry | Symmetric |
| Beam angle | 26° |

ELECTRICAL

| | |
|--------------------------|--|
| Transformer availability | Separate item |
| Transformer mounting | Remote |
| Transformer type | Electronic, Electronic dimmable, Electronic dimmable I-10V, Electronic dimmable dali |
| Emergency | Without |
| Insulation class | Class III |

PHYSICAL


| | |
|-----------------------|-------------------|
| Cutout diameter (mm) | 75 |
| Diameter (mm) | 80 |
| Recessed depth (mm) | 91 |
| Construction material | Die-cast aluminum |
| Weight (kg) | 0,24 |



Easy Kap Ø80 Fixed Optic Medium
designed by FLOS Architectural

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

| | |
|--------------------|--------|
| 03.4193.GL - 556lm | Gold |
| 03.4193.BI - 566lm | White |
| 03.4193.BU - 445lm | Blue |
| 03.4193.74 - 505lm | Black |
| 03.4193.CU - 534lm | Copper |



CERTIFICATIONS



Easy Kap Ø80 Fixed Optic Medium . Accessories

Power Supply



60.8534

Constant Current Power Supply for LED. 32W

Continuous current power supply of 32W, 230/240V - 50/60Hz with power current selected through adjustable 350/500/700 mA switch by trailing and leading edge dimming or push dimming.

Maximum length of 1.5 mm² secondary conductor (m): 10

Maximum length of 2.5 mm² secondary conductor (m): 15



60.8533

Constant Current Power Supply for LED. 25W

Continuous current power supply of 25W, 120-240V - 50/60Hz with power current selected through adjustable 350/500/700mA 1-10V switch or push dimming.

Maximum length of 1.5 mm² secondary conductor (m): 10

Maximum length of 2.5 mm² secondary conductor (m): 15



60.8847

Constant Current Power Supply for LED. 10-20W

Continuous current power supply of 10-20W, 110/240V - 50/60Hz with power current selected through adjustable 250/350/400/450/500/ 550/600/700 mA Dali switch. (Johnny 120 with accessories max 450 mA)

Maximum length of 1.5 mm² secondary conductor (m): 10

Maximum length of 2.5 mm² secondary conductor (m): 15



Easy Kap Ø80 Fixed Optic Medium
designed by FLOS Architectural

<div>Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.</div></div></div>

| | |
|--------------------|--------|
| 03.4193.GL - 556lm | Gold |
| 03.4193.B1 - 566lm | White |
| 03.4193.BU - 445lm | Blue |
| 03.4193.74 - 505lm | Black |
| 03.4193.CU - 534lm | Copper |




60.8880

Constant Current Power Supply for LED. 6W-100/14W-240V

Continuous current power supply of 6W, 100V / 14W, 240V - 50/60Hz with 500 mA supply voltage.

Maximum length of 1.5 mm² secondary conductor (m): 50

Maximum length of 2.5 mm² secondary conductor (m): 50



CERTIFICATIONS



Easy Kap Ø80 Fixed Optic Medium . Lamps



LED Array

Lamp category:

LED

Socket:

Special base

Lamp type:


LED Array



Easy Kap Ø80 Fixed Optic Medium designed by FLOS Architectural

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.

| | |
|--------------------|--------|
| 03.4193.GL - 556lm | Gold |
| 03.4193.BI - 566lm | White |
| 03.4193.BU - 445lm | Blue |
| 03.4193.74 - 505lm | Black |
| 03.4193.CU - 534lm | Copper |



CERTIFICATIONS

