FLOS

KAP Ø145 WALL-WASHER

Number of headsIMountingCeilLamps descriptionLEDLuminaire luminous fluxExtrEnvironmentIndoNotesPre-

Ceiling recessed LED Array 17W 1800 lm 2700K CRI 90 Extreme Cut-off. See reference number Indoor Pre-installation frame. To be ordered separately.

OPTICAL

Aiming Light distribution symmetry Beam angle Fixed

56°

Included

Remote

Electronic

Without

Class II

Asymmetric

ELECTRICAL

Transformer availability Transformer mounting Transformer type Emergency Insulation class

PHYSICAL

Cutout diameter (mm)	165
Diameter (mm)	145
Recessed depth (mm)	155
Construction material	Die-cast aluminum
Weight (kg)	0,94






Kap Ø145 Wall-Washer designed by FLOS Architectural

Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.

03.4589.B1 - 1189lm	White
03.4589.GL - 11311m	Gold
03.4589.BU - 980lm	Blue
	Black
03.4589.74 - 999lm	- lucit
🥥 03.4589.CU - 1117lm	Copper



CERTIFICATIONS



IP 44



FLOS

Kap Ø145 Wall-Washer . Accessories

Mounting




Installation frame Kap Ø145/ Kap Ø145 wall washer. Copper finish trim frame not available. Combine with withe or any of the other finishes according to the desired final aesthetic effect.



Kap Ø145 Wall-Washer designed by FLOS Architectural Recessed luminaire with LED light source. Remote electronic transformer 220/240V included.





Kap Ø145 Wall-Washer . Lamps



LED Array LED Socket: Special base Lamp type: LED Array CERTIFICATIONS CEC CONT CONT