

### LIGHT TUBE Ø30 DIRECT 1200 MM DIMMABLE 1-10V

**Number of heads** 

**Mounting** Track mounting

Top LED 30W 2663 lm 3000K CRI 90 Lamps description

Luminaire luminous flux See reference number

Voltage (V) 48 **Environment** Indoor

Notes


System turning fastening elements 0°-90° with a magnetic connection and mechanic security book for a transversally installation between two lines of the profile. The Light Tube are only fed by one od the ends and do not communicate current through the other end. Only compatible with DALI, I-10V, FLOS SMART CONTROL profile version.



#### Light Tube ø30 Direct 1200 mm Dimmable I-10V

designed by Vincent Van Duysen

Diffused LED light module to be installed in The Infra-Structure System.



### **OPTICAL**

**Aiming** Fixed Light distribution symmetry Symmetric 145° Beam angle

### **ELECTRICAL**

Transformer availability Separate item Transformer mounting Remote

Transformer type Electronic dimmable I-10V

**Emergency** Without





# **CERTIFICATIONS**









Flos.architectural@flos.com www.flos.com



## Light Tube ø30 Direct 1200 mm Dimmable I-10V . Lamps



**Top LED** 

Lamp category:

LED

Socket:

Special base

Lamp type:

Top LED



Light Tube ø30 Direct 1200 mm Dimmable 1-10V

designed by Vincent Van Duysen

Diffused LED light module to be installed in The Infra-Structure System.

03.8106.40.1V - 2146lm White
03.8106.14.1V - 2146lm Black



### **CERTIFICATIONS**









Flos.architectural@flos.com www.flos.com