

LIGHT SHADOW FIXED TRIM DALI VERSION 2 SPOTS OPTIC SPOT

Mounting Ceiling recessed

Lamps descriptionPower LED 5,4W 520 lm 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes Pre-installation frame not required.

OPTICAL

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 10° Spot

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable dali

Emergency Without Insulation class Class II

PHYSICAL

 Length (mm)
 77

 Recessed depth (mm)
 75

 Weight (kg)
 0,25






Light Shadow Fixed Trim Dali Version 2 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.8820.40.DA - 405lm	White / White
03.8820.14.DA - 405lm	Black / White
03.8822.40.DA - 408lm	White / Chrome
03.8822.14.DA - 408lm	Black / Chrome
03.8823.40.DA - 402lm	White / Matt Gold
03.8823.14.DA - 402lm	Black / Matt Gold
● 03.8821.40.DA - 396lm	White / Black
03.8821.14.DA - 396lm	Black / Black



CERTIFICATIONS




















Light Shadow Fixed Trim Dali Version 2 Spots Optic Spot . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Light Shadow Fixed Trim Dali Version 2 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.8820.40.DA - 405lm White / White 03.8820.14.DA - 405lm Black / White 03.8822.40.DA - 408lm White / Chrome 03.8822.14.DA - 408lm Black / Chrome 03.8823.40.DA - 402lm White / Matt Gold 03.8823.14.DA - 402lm Black / Matt Gold ■ 03.8821.40.DA - 396lm White / Black 03.8821.14.DA - 396lm Black / Black



CERTIFICATIONS















