

LIGHT SHADOW ADJUSTABLE TRIM DALI VERSION 2 SPOTS OPTIC SPOT

Mounting	Ceiling recessed
Lamps description	Power LED 5,4W 520 lm 2700K CRI 90
Luminaire luminous flux	Extreme Cut-off. See reference number
Environment	Indoor
Notes	Pre-installation frame not required.

OPTICAL

Aiming	Adjustable
Light distribution symmetry	Symmetric
Beam angle	10° Spot

ELECTRICAL

Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class II

PHYSICAL

Recessed depth (mm)	75
Weight (kg)	0,25





Light Shadow Adjustable Trim Dali Version 2 Spots Optic Spot



designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

- 03.8884.40.DA - 405lm White / White
- 03.8884.14.DA - 405lm Black / White
- ◐ 03.8886.40.DA - 408lm White / Chrome
- ◑ 03.8886.14.DA - 408lm Black / Chrome
- ◒ 03.8887.40.DA - 402lm White / Matt Gold
- ◓ 03.8887.14.DA - 402lm Black / Matt Gold
- ◔ 03.8885.40.DA - 396lm White / Black
- ◕ 03.8885.14.DA - 396lm Black / Black



CERTIFICATIONS



Light Shadow Adjustable Trim Dali Version 2 Spots Optic Spot . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:






Power LED




Light Shadow Adjustable Trim Dali Version 2 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

-  03.8884.40.DA - 405lm White / White
-  03.8884.14.DA - 405lm Black / White
-  03.8886.40.DA - 408lm White / Chrome
-  03.8886.14.DA - 408lm Black / Chrome
-  03.8887.40.DA - 402lm White / Matt Gold
-  03.8887.14.DA - 402lm Black / Matt Gold
-  03.8885.40.DA - 396lm White / Black
-  03.8885.14.DA - 396lm Black / Black



CERTIFICATIONS

