FLOS

LIGHT SHADOW ADJUSTABLE TRIM DALI VERSION 4 SPOTS OPTIC SPOT

Adjustable

Symmetric

10° Spot

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 10,8W 1120 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor Pre-installation frame not required.

OPTICAL

Aiming Light distribution symmetry Beam angle

ELECTRICAL

- Transformer availability Transformer mounting Transformer type Emergency Insulation class
- Included Remote Electronic dimmable dali Without Class II

PHYSICAL

Recessed depth (mm)	
Weight (kg)	

75 0,34







Light Shadow Adjustable Trim Dali Version 4 Spots Optic Spot designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

🖉 03.8896.40.DA - 864lm	White / White
Ø3.8896.14.DA - 864lm	Black / White
alim 03.8898.40.DA - 8711m	White / Chrome
🚺 03.8898.14.DA - 8711m	Black / Chrome
🥖 03.8899.40.DA - 858lm	White / Matt Gold
🏉 03.8899.14.DA - 858lm	Black / Matt Gold
03.8897.40.DA - 846lm	White / Black
03.8897.14.DA - 846lm	Black / Black



CERTIFICATIONS \overbrace{C} $\overbrace{PENDING}$ \overbrace{F} $\overbrace{B50^{\circ}}$ $\overbrace{B50^{\circ}}$ $\overbrace{B0^{\circ}}$ \overbrace{D} \overbrace{P} $\overbrace{A44}$



FLOS

Light Shadow Adjustable Trim Dali Version 4 Spots Optic Spot . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.8896.40.DA - 864lm	White / White
Ø3.8896.14.DA - 864lm	Black / White
🖉 03.8898.40.DA - 8711m	White / Chrome
03.8898.14.DA - 8711m	Black / Chrome
🥖 03.8899.40.DA - 858lm	White / Matt Gold
🏉 03.8899.14.DA - 858lm	Black / Matt Gold
🕑 03.8897.40.DA - 846lm	White / Black
03.8897.14.DA - 846lm	Black / Black

