FLOS

LIGHT SHADOW ADJUSTABLE NO TRIM DALI VERSION 2 SPOTS OPTIC SPOT

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 5,4W 520 Im 2700K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Light distribution symmetry Beam angle

ELECTRICAL

- Transformer availability Transformer mounting Transformer type Emergency Insulation class
- Included Remote Electronic dimmable dali Without Class II

PHYSICAL

Recessed depth (mm)	
Weight (kg)	

75 0,25

Adjustable

Symmetric

10° Spot







Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Spot


designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.8916.40.DA - 405lm	White / White
03.8916.14.DA - 405lm	Black / White
alian 03.8918.40.DA - 408lm	White / Chrome
🖉 03.8918.14.DA - 408lm	Black / Chrome
🥖 03.8919.40.DA - 402lm	White / Matt Gold
🏉 03.8919.14.DA - 402lm	Black / Matt Gold
🟉 03.8917.40.DA - 396lm	White / Black
03.8917.14.DA - 396lm	Black / Black







FLOS

Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Spot . Accessories





The state of the s

08.0515.00

Pre-installation frame. Adjustable No Trim 2L

08.0059.90

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Spot . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.8916.40.DA - 405lm	White / White
03.8916.14.DA - 405lm	Black / White
🖉 03.8918.40.DA - 408lm	White / Chrome
🚺 03.8918.14.DA - 408lm	Black / Chrome
🥖 03.8919.40.DA - 402lm	White / Matt Gold
🏉 03.8919.14.DA - 402lm	Black / Matt Gold
🟉 03.8917.40.DA - 396lm	White / Black
Ø3.8917.14.DA - 396lm	Black / Black

