

LIGHT SHADOW ADJUSTABLE NO TRIM DALI VERSION 2 SPOTS OPTIC SPOT

Mounting Ceiling recessed

Lamps descriptionPower LED 5,4W 560 lm 3000K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Adjustable
Light distribution symmetry Symmetric
Beam angle 10° Spot

ELECTRICAL

Transformer availability Included Transformer mounting Remote

Transformer type Electronic dimmable dali

Emergency Without Insulation class Class II

PHYSICAL

 Recessed depth (mm)
 75

 Weight (kg)
 0,25






Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.8920.40.DA - 432lm White / White 03.8920.14.DA - 432lm Black / White 03.8922.40.DA - 435lm White / Chrome 03.8922.14.DA - 435lm Black / Chrome → 03.8923.40.DA - 429lm White / Matt Gold 03.8923.14.DA - 429lm Black / Matt Gold ■ 03.8921.40.DA - 423lm White / Black 03.8921.14.DA - 423lm Black / Black



CERTIFICATIONS






















Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Spot . Accessories

Mounting





08.0515.00

08.0059.90

Pre-installation frame. Adjustable No Trim 2L Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim pre-installation frames.

Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Spot . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Light Shadow Adjustable No Trim Dali Version 2 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.8920.40.DA - 432lm White / White 03.8920.14.DA - 432lm Black / White 03.8922.40.DA - 435lm White / Chrome 03.8922.14.DA - 435lm Black / Chrome 03.8923.40.DA - 429lm White / Matt Gold 03.8923.14.DA - 429lm Black / Matt Gold ■ 03.8921.40.DA - 423lm White / Black 03.8921.14.DA - 423lm Black / Black



CERTIFICATIONS

















