

LIGHT SHADOW ADJUSTABLE NO TRIM DALI VERSION 12 SPOTS OPTIC SPOT

Mounting Ceiling recessed

Lamps descriptionPower LED 32,4W 3120 lm 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes It requires an pre-installation frame, to be ordered separately

OPTICAL

Aiming Adjustable
Light distribution symmetry Symmetric
Beam angle 10° Spot

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable dali

Emergency Without Insulation class Class II

PHYSICAL

Recessed depth (mm) 75 Weight (kg) 0,66





Light Shadow Adjustable No Trim Dali Version 12 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.8940.40.DA - 2430lm White / White


03.8940.14.DA - 2430lm Black / White

03.8942.40.DA - 2447lm White / Chrome

03.8942.14.DA - 2447lm Black / Chrome

03.8943.40.DA - 2411Im White / Matt Gold
03.8943.14.DA - 2411Im Black / Matt Gold

03.8941.40.DA - 2379lm White / Black 03.8941.14.DA - 2379lm Black / Black



CERTIFICATIONS






















Light Shadow Adjustable No Trim Dali Version 12 Spots Optic Spot . Accessories

Mounting





08.0518.00

08.0059.90

Pre-installation frame. Adjustable No Trim 12L Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim pre-installation frames.

Light Shadow Adjustable No Trim Dali Version 12 Spots Optic Spot . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED



Light Shadow Adjustable No Trim Dali Version 12 Spots Optic Spot

designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.8940.40.DA - 2430lm White / White

03.8940.14.DA - 2430lm Black / White

03.8942.40.DA - 2447lm White / Chrome


03.8942.14.DA - 2447lm Black / Chrome

03.8943.40.DA - 2411lm White / Matt Gold

03.8943.14.DA - 2411lm Black / Matt Gold

03.8941.40.DA - 2379lm White / Black

03.8941.14.DA - 2379lm Black / Black



CERTIFICATIONS

















