

LIGHT SHADOW OPTIC SPOT DALI VERSION

Number of heads	1
Mounting	Track mounting
Lamps description	Power LED 10,8W 4 x 280 lm 3000K CRI 90
Luminaire luminous flux	Extreme Cut-off. See reference number
Voltage (V)	24
Environment	Indoor
Notes	Installation frame not required.



OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	10° Spot

Light Shadow Optic Spot Dali Version
designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.


ELECTRICAL

Transformer availability	Separate item
Transformer mounting	Remote
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class III



- 03.8953.40.DA - 846lm White / Black
- 03.8953.14.DA - 846lm Black / Black
- 03.8952.40.DA - 864lm White / White
- 03.8952.14.DA - 864lm Black / White
- 03.8954.40.DA - 871lm White / Chrome
- 03.8954.14.DA - 871lm Black / Chrome
- 03.8955.40.DA - 858lm White / Matt Gold
- 03.8955.14.DA - 858lm Black / Matt Gold

PHYSICAL

Weight (kg)	0,34
--------------------	------



CERTIFICATIONS



Light Shadow Optic Spot Dali Version . Lamps




Power LED

Lamp category:
LED









Socket:
Special base


Lamp type:
Power LED



Light Shadow Optic Spot Dali Version
designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

-  03.8953.40.DA - 846lm White / Black
-  03.8953.14.DA - 846lm Black / Black
-  03.8952.40.DA - 864lm White / White
-  03.8952.14.DA - 864lm Black / White
-  03.8954.40.DA - 871lm White / Chrome
-  03.8954.14.DA - 871lm Black / Chrome
-  03.8955.40.DA - 858lm White / Matt Gold
-  03.8955.14.DA - 858lm Black / Matt Gold



CERTIFICATIONS

