

# LIGHT SHADOW FIXED TRIM 2 SPOTS OPTIC FLOOD

**Mounting** Ceiling recessed

Power LED 5,4W 520 lm 2700K CRI 90 Lamps description Luminaire luminous flux Extreme Cut-off. See reference number

**Environment** Indoor

Notes Pre-installation frame not required.

### **OPTICAL**

**Aiming** Fixed Light distribution symmetry Symmetric Beam angle 33° Flood

#### **ELECTRICAL**

Transformer availability Included Transformer mounting Remote Transformer type Electronic **Emergency** Without **Insulation class** Class II

#### **PHYSICAL**

Length (mm) 77 Recessed depth (mm) 75 Weight (kg) 0,25






#### **Light Shadow Fixed Trim 2 Spots Optic Flood**

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.9105.40 - 394lm	White / White
<b>0</b> 3.9105.14 - 394lm	Black / White
03.9107.40 - 403lm	White / Chrome
03.9107.14 - 403lm	Black / Chrome
03.9108.40 - 390lm	White / Matt Gold
03.9108.14 - 390lm	Black / Matt Gold
<b>33.9106.40 - 383lm</b>	White / Black
03.9106.14 - 383lm	Black / Black



## **CERTIFICATIONS**




















## **Light Shadow Fixed Trim 2 Spots Optic Flood . Lamps**



**Power LED** 

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




## Light Shadow Fixed Trim 2 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included.

03.9105.40 - 394lm	White / White
<b>0</b> 3.9105.14 - 394lm	Black / White
03.9107.40 - 403lm	White / Chrome
03.9107.14 - 403lm	Black / Chrome
03.9108.40 - 390lm	White / Matt Gold
<b>0</b> 3.9108.14 - 390lm	Black / Matt Gold
<b>3.9106.40 - 383lm</b>	White / Black
03.9106.14 - 383lm	Black / Black



## **CERTIFICATIONS**















