

LIGHT SHADOW FIXED TRIM DALI VERSION 8 SPOTS OPTIC FLOOD

Mounting	Ceiling recessed
Lamps description	Power LED 21,6W 2240 lm 3000K CRI 90
Luminaire luminous flux	Extreme Cut-off. See reference number
Environment	Indoor
Notes	Pre-installation frame not required.

OPTICAL

Aiming	Fixed
Light distribution symmetry	Symmetric
Beam angle	33° Flood

ELECTRICAL

Transformer availability	Included
Transformer mounting	Remote
Transformer type	Electronic dimmable dali
Emergency	Without
Insulation class	Class II

PHYSICAL

Length (mm)	287
Recessed depth (mm)	75
Weight (kg)	0,50





Light Shadow Fixed Trim Dali Version 8 Spots Optic Flood



designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

- 03.9155.40.DA - 1682lm White / White
- 03.9155.14.DA - 1682lm Black / White
- ◐ 03.9157.40.DA - 1720lm White / Chrome
- ◑ 03.9157.14.DA - 1720lm Black / Chrome
- ◒ 03.9158.40.DA - 1667lm White / Matt Gold
- ◓ 03.9158.14.DA - 1667lm Black / Matt Gold
- ◔ 03.9156.40.DA - 1634lm White / Black
- ◕ 03.9156.14.DA - 1634lm Black / Black



CERTIFICATIONS



Light Shadow Fixed Trim Dali Version 8 Spots Optic Flood . Lamps



Power LED

Lamp category:
LED

Socket:
Special base

Lamp type:
Power LED




Light Shadow Fixed Trim Dali Version 8 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

- 03.9155.40.DA - 1682lm White / White
- 03.9155.14.DA - 1682lm Black / White
- 03.9157.40.DA - 1720lm White / Chrome
- 03.9157.14.DA - 1720lm Black / Chrome
- 03.9158.40.DA - 1667lm White / Matt Gold
- 03.9158.14.DA - 1667lm Black / Matt Gold
- 03.9156.40.DA - 1634lm White / Black
- 03.9156.14.DA - 1634lm Black / Black



CERTIFICATIONS

