

LIGHT SHADOW FIXED NO TRIM DALI VERSION 4 SPOTS OPTIC FLOOD

Mounting Ceiling recessed

Lamps descriptionPower LED 10,8W 1040 lm 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 33° Flood

ELECTRICAL


Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable dali

Emergency Without Insulation class Class II

PHYSICAL

Length (mm) 140
Recessed depth (mm) 75
Weight (kg) 0,34






Light Shadow Fixed No Trim Dali Version 4 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9225.40.DA - 788lm White / White 03.9225.14.DA - 788lm Black / White 03.9227.40.DA - 806lm White / Chrome 03.9227.14.DA - 806lm Black / Chrome → 03.9228.40.DA - 781Im White / Matt Gold 03.9228.14.DA - 781lm Black / Matt Gold 03.9226.40.DA - 765lm White / Black 03.9226.14.DA - 765lm Black / Black



CERTIFICATIONS




















Light Shadow Fixed No Trim Dali Version 4 Spots Optic Flood . Accessories

Mounting





08.0511.00

08.0052.90

Pre-installation frame. Fixed No Trim 4L

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim pre-installation frames.

Light Shadow Fixed No Trim Dali Version 4 Spots Optic Flood . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Light Shadow Fixed No Trim Dali Version 4 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9225.40.DA - 788lm White / White 03.9225.14.DA - 788lm Black / White 03.9227.40.DA - 806lm White / Chrome 03.9227.14.DA - 806lm Black / Chrome 03.9228.40.DA - 781lm White / Matt Gold 03.9228.14.DA - 781lm Black / Matt Gold ■ 03.9226.40.DA - 765lm White / Black 03.9226.14.DA - 765lm Black / Black



CERTIFICATIONS















