FLOS

LIGHT SHADOW FIXED NO TRIM DALI VERSION 8 SPOTS OPTIC MEDIUM

Fixed

Symmetric

23° Medium

Mounting Lamps description Luminaire luminous flux Environment Notes Ceiling recessed Power LED 21,6W 2240 Im 3000K CRI 90 Extreme Cut-off. See reference number Indoor It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Light distribution symmetry Beam angle

ELECTRICAL

| Transformer availability | Included |
|--------------------------|--------------------------|
| Transformer mounting | Remote |
| Transformer type | Electronic dimmable dali |
| Emergency | Without |
| Insulation class | Class II |
| | |

PHYSICAL

| Length (mm) | 280 |
|---------------------|------|
| Recessed depth (mm) | 75 |
| Weight (kg) | 0,50 |







Light Shadow Fixed No Trim Dali Version 8 Spots Optic Medium


designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

| 03.9250.40.DA - 1686lm | White / White |
|--------------------------|-------------------|
| ♥ 03.9250.14.DA - 1686lm | Black / White |
| 🖉 03.9252.40.DA - 1709lm | White / Chrome |
| 03.9252.14.DA - 1709lm | Black / Chrome |
| 🥖 03.9253.40.DA - 1678lm | White / Matt Gold |
| 💋 03.9253.14.DA - 1678lm | Black / Matt Gold |
| 03.9251.40.DA - 1656lm | White / Black |
| 03.9251.14.DA - 1656lm | Black / Black |
| | |







FLOS

Light Shadow Fixed No Trim Dali Version 8 Spots Optic Medium . Accessories

Mounting



08.0512.00

Pre-installation frame. Fixed No Trim 8L



08.0052.90

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Fixed No Trim Dali Version 8 Spots Optic Medium . Lamps



Power LED LED Socket: Special base Lamp type: Power LED



Light Shadow Fixed No Trim Dali Version 8 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included.

| 03.9250.40.DA - 1686lm | White / White |
|---------------------------------|-------------------|
| Ø3.9250.14.DA - 1686lm | Black / White |
| align: 03.9252.40.DA - 1709lm 🖉 | White / Chrome |
| 03.9252.14.DA - 1709lm | Black / Chrome |
| 🥖 03.9253.40.DA - 1678lm | White / Matt Gold |
| 💋 03.9253.14.DA - 1678lm | Black / Matt Gold |
| 🟉 03.9251.40.DA - 1656lm | White / Black |
| 03.9251.14.DA - 1656lm | Black / Black |
| | |

