

LIGHT SHADOW FIXED NO TRIM DALI VERSION 12 SPOTS OPTIC MEDIUM

Mounting Ceiling recessed

Lamps descriptionPower LED 32,4W 3120 lm 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 23° Medium

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable dali

Emergency Without Insulation class Class II

PHYSICAL

 Length (mm)
 420

 Recessed depth (mm)
 75

 Weight (kg)
 0,66





designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.9260.40.DA - 2369lm White / White

03.9260.14.DA - 2369lm Black / White

03.9262.40.DA - 2402lm White / Chrome


03.9262.14.DA - 2402lm Black / Chrome

03.9263.40.DA - 2358lm White / Matt Gold

03.9263.14.DA - 2358lm Black / Matt Gold

03.9261.40.DA - 2327lm White / Black

03.9261.14.DA - 2327lm Black / Black



CERTIFICATIONS



















Light Shadow Fixed No Trim Dali Version 12 Spots Optic Medium . Accessories

Mounting





08.0513.00

08.0052.90

Pre-installation frame. Fixed No Trim 12L

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Fixed No Trim Dali Version 12 Spots Optic Medium . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED



Light Shadow Fixed No Trim Dali Version 12 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.9260.40.DA - 2369lm White / White

03.9260.14.DA - 2369lm Black / White

03.9262.40.DA - 2402lm White / Chrome


03.9262.14.DA - 2402lm Black / Chrome

03.9263.40.DA - 2358lm White / Matt Gold

03.9263.14.DA - 2358lm Black / Matt Gold

03.9261.40.DA - 2327lm White / Black

03.9261.14.DA - 2327lm Black / Black



CERTIFICATIONS















