

LIGHT SHADOW FIXED NO TRIM DALI VERSION 12 SPOTS OPTIC FLOOD

Mounting Ceiling recessed

Lamps descriptionPower LED 32,4W 3120 lm 2700K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 33° Flood

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable dali

Emergency Without Insulation class Class II

PHYSICAL

 Length (mm)
 420

 Recessed depth (mm)
 75

 Weight (kg)
 0,66



Light Shadow Fixed No Trim Dali Version 12 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.9265.40.DA - 2364lm White / White

03.9265.14.DA - 2364lm Black / White

03.9267.40.DA - 2417lm White / Chrome


03.9267.14.DA - 2417lm Black / Chrome

03.9268.40.DA - 2343lm White / Matt Gold

03.9268.14.DA - 2343lm Black / Matt Gold

03.9266.40.DA - 2296lm White / Black

03.9266.14.DA - 2296lm Black / Black



CERTIFICATIONS




















Light Shadow Fixed No Trim Dali Version 12 Spots Optic Flood . Accessories

Mounting





08.0513.00

08.0052.90

Pre-installation frame. Fixed No Trim 12L

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Fixed No Trim Dali Version 12 Spots Optic Flood . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED



Light Shadow Fixed No Trim Dali Version 12 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included.

03.9265.40.DA - 2364lm White / White

03.9265.14.DA - 2364lm Black / White

03.9267.40.DA - 2417lm White / Chrome


03.9267.14.DA - 2417lm Black / Chrome

03.9268.40.DA - 2343lm White / Matt Gold

03.9268.14.DA - 2343lm Black / Matt Gold

03.9266.40.DA - 2296lm White / Black

03.9266.14.DA - 2296lm Black / Black



CERTIFICATIONS















