

LIGHT SHADOW ADJUSTABLE TRIM DALI VERSION 4 SPOTS OPTIC MEDIUM

Mounting Ceiling recessed

Lamps descriptionPower LED 10,8W 1120 lm 3000K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoor

Notes Pre-installation frame not required.

OPTICAL

Aiming Adjustable
Light distribution symmetry Symmetric
Beam angle 23° Medium

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable dali

Emergency Without Insulation class Class II

PHYSICAL

 Recessed depth (mm)
 75

 Weight (kg)
 0,34






Light Shadow Adjustable Trim Dali Version 4 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9330.40.DA - 843lm White / White 03.9330.14.DA - 843lm Black / White 03.9332.40.DA - 855lm White / Chrome 03.9332.14.DA - 855lm Black / Chrome → 03.9333.40.DA - 839lm White / Matt Gold 03.9333.14.DA - 839lm Black / Matt Gold ■ 03.9331.40.DA - 828lm White / Black 03.9331.14.DA - 828lm Black / Black



CERTIFICATIONS






















Light Shadow Adjustable Trim Dali Version 4 Spots Optic Medium . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Light Shadow Adjustable Trim Dali Version 4 Spots Optic Medium

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9330.40.DA - 843lm White / White 03.9330.14.DA - 843lm Black / White 03.9332.40.DA - 855lm White / Chrome 03.9332.14.DA - 855lm Black / Chrome 03.9333.40.DA - 839lm White / Matt Gold 03.9333.14.DA - 839lm Black / Matt Gold **△** 03.9331.40.DA - 828lm White / Black 03.9331.14.DA - 828lm Black / Black



CERTIFICATIONS

















